

INDIAN INSTITUTE OF TECHNOLOGY DELHI

HAUZ KHAS, NEW DELHI – 110016

NOTICE INVITING E-TENDER

IITD/WORKS (SP- 4642)/2024

Executive Engineer (Electrical Division-I), Indian Institute of Technology Delhi, Hauz Khas, New Delhi – 110016, Ph. No. 011-2654 8437 on behalf of Board of Governors invites online Item Rate Tender from the "CPWD, MES, BSNL, Railways Enlisted Contractors of Composite Category in appropriate class and specialized agency" for providing and installations of lifts as per details given below.

1	Name of work	:	Replacement of 5 x 8 Passenger Lifts at
			different places in IIT Delhi.
2	NIT No.	:	0276/121/IITD/EW/2023-24
3	Estimated Cost (₹)	:	1,06,07,941.00
4	Earnest Money Deposit (₹)	:	2,12,159.00 (No exemption allowed)
5	Period of completion	:	270 days
6	Last date & time of bid submission	:	Upto 3 PM of 29.05.2024
7	Performance Bank Guarantee	:	5 percent of the tendered amount

The bid forms and other details may be downloaded from Central Public Procurement Portal (http://eprocure.gov.in/eprocure/app). Aspiring bidders who have not enrolled / registered in e-procurement should enrol / register themselves before participating through web site http://eprocure.gov.in/eprocure/app. The portal enrolment is free of cost. Bidders are advised to go through instructions provided at "Instructions for online bid submission."

Bidders can access quotation / tender documents on the website (for searching in the NIC site), kindly go to quotation search option and type 'IIT'. Thereafter, click on "GO" button to view all IIT quotations. Select the appropriate quotation / tender and fill them with all relevant information and submit the completed Quotation / Tender document online on the website http://eprocure.gov.in/eprocure/app as per the schedule given in the next page.

No manual bids will be accepted. All bids (both Technical & Financial) should be submitted in the e-procurement portal.

Executive Engineer (ED-I) For & on behalf of BOG, IIT Delhi

Page 1 of 64



****3 to e[®]!"

Ch. Head: Renovation (Research Facility and Housing)/35.01.02(IOE) &

Operation and maintenance of Building / 31.06.30 (AMC)

Work Code: (2021/006/0276) & (2021/006/0277) (AMC)

Copy to:-

- 1. Assistant Executive Engineer (E)
- 2. D.A. (Works Accounts)
- 3. D.R. (A/C)
- 4. A.R. (Store Purchase Section)
- 5. Notice Board
- 6. Website Administrator, IIT Delhi
- 7. Office copy

<u>INDEX</u>

Sr.	Description	Pa	ge
No.	-	From	То
1	Schedule of NIT	03	04
2	Instruction for online bid submission	04	07
3	Information & instruction to bidders	08	10
4	List of mandatory Document	11	12
5	IITD 6 Form	13	15
6	Integrity Pact	16	22
7	IITD – 7/8 Form	23	24
8	Proforma of Schedule	25	29
9	9 Commercial & Additional conditions		36
10	Additional Specification and Special conditions	37	50
11	Technical Particulars Annexure X1, X2 & H	51	54
12	12 Instruction to be displayed		55
13	Declaration (Annexure – 1)	56	56
14	Bid Submission Check List	57	58
15	Schedule of Quantity	59	64



To act.

SCHEDULE

1	Name of organisation	:	Indian Institute of Technology Delhi
2	Tender / Quotation type (open / limited	:	Open
	/ EOI / auction / single)		·
3	Tender / Quotation category (services	:	Goods & Works
	/ goods / works)		
4	Type of Contract (work / supply /	:	Work & Supply
	auction / service / buy / empanelment /		
	sell)		
5	Form of contract (IITD – 7/8)	:	IITD – 8
6	Work Category (civil / electrical / fleet	:	Electrical
	management / computer systems)		
7	Is multi-currency allowed?	:	No
8	Date of publishing / issue / start	:	20.05.2024 at 03:00 PM
9	Document download start date	:	20.05.2024 at 03:00 PM
10	Document download end date	:	29.05.2024 upto 03:00 PM
11	Date & time of pre-bid meeting	:	No pre-bid meeting be held
12	Venue of pre-bid meeting	:	NIL
13	Last date & time of uploading of bids	:	Upto 03.00 PM of 29.05.2024
14	Date & time of opening of Technical	:	30.05.2024 at 15.00 PM
	bids		
15	Tender fee	:	Free of cost
16	Earnest Money Deposit (EMD)	:	Rs.2,12,159.00
			To be paid through RTGS / NEFT.
			IIT Delhi Bank details are as under:
			Name of Bank A/C: IITD Revenue A/C
			SBI A/C No. – 10773572622
			Name of Bank: State Bank of India, IIT
			Delhi, Hauz Khas, New Delhi – 110016 IFSC Code: SBIN0001077
			MICR Code: 110002156
			Swift No.: SBININBB547
			This is mandatory that UTR number is
			provided in the online quotation / bid
			(Refer UTR column in the Declaration
			sheet at Annexure – 1)
			OR
			In the form of Banker's Cheque or Demand
			Draft or FDR of scheduled bank in favour
			of Registrar, IIT Delhi (scanned copy of
			the same to be uploaded with the bid, date
			of issue shall be within the NIT period)
17	No. of bids / covers (1 / 2 / 3 / 4)	:	2



18	Address for communication		Executive Engineer (ED-I), Works Department, IIT Delhi, Hauz Khas, New Delhi - 110016			
19	Contact No.	:	011 2654 8437			
20	e-mail address	:	aashish@admin.iitd.ac.in;			

INSTRUCTIONS FOR ONLINE BID SUBMISSION

As per the directives of Department of Expenditure, this quotation / tender document has been published on the Central Public Procurement Portal (URL: http://eprocure.gov.in/eprocure/app). The bidders are required to submit softcopies of their bids electronically on the CPP portal, using valid Digital Signature Certificates (DSC). The instructions given below are meant to assist the bidders in registering on the CPP portal, prepare their bids in accordance with the requirements and submitting their bids online on the CPP portal.

More information useful for submitting online bids on the CPP portal may be obtained at http://eprocure.gov.in/eprocure/app

REGISTRATION

- 1. Bidders are required to enrol on the e-procurement module of the Central Public Procurement portal (URL: http://eprocure.gov.in/eprocure/app) by clicking on the link, "click here to enrol". Enrolment on the CPP portal is free of charge.
- 2. As part of the enrolment process, the bidders will be required to choose a unique user name and assign a password for their accounts.
- 3. Bidders are advised to register their valid e-mail address and mobile number as part of the registration process. These would be used for any communication from the CPP Portal.
- 4. Upon enrolment, the bidders will be required to register their valid Digital Signature Certificate (class 2 or class 3 certificates with signing key usage) issued by any certifying authority recognised by CCA India (e.g. Sify / TCS / nCode / eMudhra etc.) with their profile.
- 5. Only one valid DSC should be registered by a bidder. Please note that bidders are responsible to ensure that they do not lend their DSCs to others which may lead to misuse.
- 6. Bidder then logs into the site through the secured log-in by entering their user ID / password and the password of the DSC / eToken.

Page **4** of **64**



.....

SEARCHING FOR TENDER DOCUMENTS

- 1. There are various search options built in the CPP portal to facilitate bidders to search active tenders by several parameters. These parameters could include tender ID, organisation name, location, date, value, etc. There is also an option of advanced search for tenders, wherein the bidders may combine a number of search parameters such as organisation name, form of contract, location, date, other keywords etc. to search for a tender published on the CPP portal.
- 2. Once the bidders have selected the tenders they are interested in, they may download the required documents / tender schedules. The tenders can be moved to the respective "My Tenders" folder. This would enable the CPP portal to intimate the bidders through SMS / e-mail in case there is any corrigendum issued to the tender document.
- 3. The bidder should make a note of the unique Tender ID assigned to each other, in case they want to obtain any clarification / help from the Helpdesk.

PREPARATION OF BIDS

- 1. Bidder should take into account any corrigendum published on the tender document before submitting their bids.
- 2. Please go through the tender advertisement and the tender document carefully to understand the documents required to be submitted as part of the bids. Please note the number of covers in which the bid documents have to be submitted. Any deviations from these may lead to rejection of the bids.
- 3. Bidder, in advance, should get ready the bid documents to be submitted as indicated in the tender document / schedule and generally, they can be in PDF / XLS / RAR / DWF formats. Bid documents may be scanned with 100 dpi with black & white option.
- 4. To avoid the time and effort required in uploading the same set of standard documents which are required to be submitted as a part of every bid, a provision of uploading such standard documents (e.g. PAN card copy, annual reports, auditor's certificates, etc.) has been provided to the bidders. Bidders can use "My Space" area available to them to upload such documents. These documents may be directly submitted from the "My Space" area while submitting a bid, and need not be uploaded again and again. This will lead to a reduction in the time required for bid submission process.

SUBMISSION OF BIDS

1. Bidder should log into the site well in advance for bid submission so that he / she upload the bid in time i.e. on or before the bid submission time. Bidder will be responsible for any delay due to other issues.

Page 5 of 64



- 2. The bidder has to digitally sign and upload the required bid documents one by one as indicated in the tender document.
- 3. Bidder has to select the payment option as "on-line" to pay the tender fee / EMD as applicable and enter details of the instrument. Whenever, EMD / Tender fees is sought, bidders need to pay the tender fee and EMD separately on-line through RTGS (Refer to Schedule, Page no. 3)
- 4. A standard BOQ Format has been provided with the tender document to be filled by all the bidders. Bidders are requested to note that they should necessarily submit their financial bids in the format provided and no other format is acceptable. Bidders are required to download the BOQ file, open it and complete the white coloured [unprotected] cells with their respective financial quotes and other details (such as name of the bidder). No other cells should be changed. Once the details have been completed, the bidder should save it online, without changing the filename. If the BOQ file is found to be modified by the bidder, the bid will be rejected.

OR

In some cases financial bids can be submitted in PDF format as well (in lieu of BOQ).

- 5. The server time (which is displayed on the bidders' dashboard) will be considered as the standard time for referencing the deadlines for submission of the bids by the bidders, opening of bids etc. The bidders should follow this time during bid submission.
- 6. All the documents being submitted by the bidders would be encrypted using PKI encryption techniques to ensure the secrecy of the data. The data entered cannot be viewed by unauthorised persons until the time of bid opening. The confidentiality of the bids is maintained using the secured Socket Layer 128 bit encryption technology. Data storage encryption of sensitive fields is done.
- 7. The uploaded tender documents become readable only after the tender opening by the authorised bid openers.
- 8. Upon the successful and timely submission of bids, the portal will give a successful bid submission message & a bid summary will be displayed with the bid no, and the date & time of submission of the bid with all other relevant details.
- 9. Kindly add scanned PDF of all relevant documents in a single PDF file of compliance sheet.

ASSISTANCE TO BIDDERS

1. Any queries relating to tender document and the terms and conditions contained therein should be addressed to the tender inviting authority for a tender or the relevant contact person indicated in the tender.

Page 6 of 64



 Any queries relating to the process of online bid submission or queries relating to CPP portal in general may be directed to the 24 x 7 CPP Portal Help Desk. The contact number of the helpdesk is 18002337315.

GENERAL INSTRUCTIONS TO THE BIDDERS

- 1. The tenders will be received online through portal https://eprocure.gov.in/eprocure/app. In the technical bids, the bidders are required to upload all the documents in PDF format.
- 2. Possession of a valid class II / III Digital Signature Certificate (DSC) in the form of smart card / e-token in the company's name is a prerequisite for registration and participating in the bid submission activities through https://eprocure.gov.in/eprocure/app. Digital Signature Certificates can be obtained from the authorised certifying agencies, details of which are available in the website https://eprocure.gov.in/eprocure/app under the link "Information about DSC".
- 3. Tenderers are advised to follow the instructions provided in the "Instructions to the tenderer" for the e-submission of the bids online through the Central Public Procurement Portal for e-procurement at https://eprocure.gov.in/eprocure/app.

Page 7 of 64



INFORMATION & INSTRUCTION TO BIDDERS FOR E-TENDERING

Executive Engineer (ED-I), Indian Institute of Technology Delhi, Hauz Khas, New Delhi – 110016, Ph. No. 011-2654 8437 on behalf of Board of Governors invites online Item Rate Tender from the "CPWD, MES, BSNL, Railways Enlisted Contractors of Composite Category in appropriate class and specialized agency" as per details given below:

;	Sr. No.	NIT No.	Name of Work & Location	Estimated cost put to bid (₹)	Earnest money (₹)	Period of completion	Last date & time of submission of bid	Time & date of opening of Technical Bid	Time & date of opening of Financial Bid
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
	1	0276/121/IITD/EW/2023-24	Replacement of 5 x 8 Passenger Lifts at different places in IIT Delhi.	1,06,07,941.00	2,12,159.00	270 days	Upto 03.00 PM of 29.05.2024	30.05.2024 at 03.00 PM	To be decided after assessing Technical Bids

- 1. The bidder whose bid is accepted shall be required to submit a performance guarantee of 5 percent of the tendered amount in the form of Bank Guarantee or FDR from a nationalised / scheduled bank within the period specified in Schedule F. in case the bidder fails to deposit the said performance guarantee within the period as indicated in Schedule 'F', including the extended period if any, the Earnest Money deposited by the bidder shall be forfeited automatically without any notice to the bidder. The Performance Guarantee shall initially be kept valid upto the stipulated date of completion plus sixty days beyond that.
- 2. Contractors who fulfil the following requirements shall be eligible to apply. Joint ventures are not accepted.
 - a. Should have satisfactorily completed the works as mentioned below during the last Seven years ending previous day of last date of submission of bids.

Page 8 of 64



- i. **Three** similar works each costing not less than **Rs.42,44,000.00**, or **two** similar works each costing not less than **Rs.63,65,000.00**, or one similar work costing not less than **Rs.84,87,000.00** (all figures rounded to nearest thousand)
- ii. **Earnest money** of Rs. 2,12,159.00 to be deposited either online or scanned copy of Banker's Cheque or Demand Draft or FDR as indicated in the Schedule at pg 3.
- 3. The value of executed work shall be brought to current costing level by enhancing the actual value of work at simple rate of 7% per annum; calculated from the date of completion to last date of submission of financial bid.
- 4. Similar work means Supply, Installation, Testing and Commissioning of Passenger Lifts including associated E&M and Civil works in buildings.
- 5. Work means work done with some Central Government Department / State Government Department/ Central Autonomous Body / State Autonomous Body / Central Public Sector Undertaking / State Public Sector Undertaking / City Development Authority / Municipal Corporation of City formed under any Act by Central / State Government and published in Central / State Gazette.
- 6. Completion certificates are required to be got issued by an officer not below the rank of Executive Engineer of similar works completed by the Firm. The work experience certificates submitted by the bidders shall clearly indicate that:
 - a. The similar work executed shall be as per '4' above
 - b. The completed cost of the work
 - c. Actual date of completion of the work
- 7. IITD is committed to follow the principle of transparency, equity and competitiveness in public procurement. Before submission of bid, each bidder should sign integrity pact at respective places and submit the bid. If duly signed integrity pact is not submitted by bidder, such bid shall not be considered.
- 8. The intending bidder must read the terms and conditions [both commercial & Additional] & IITD 6 carefully which will be the part of the Contract. He should only submit his bid if he considers himself eligible and he is in possession of all the documents required.
- **9.** Information and Instructions for bidders posted on website shall form part of bid document.
- 10. The bid document consisting of plans, specifications, the schedule of quantities of various types of items to be executed and the set of terms and conditions of the contract to be complied with and other necessary documents can be seen and downloaded from website e-procure.gov.in free of cost.
- 11. But the bid can only be submitted after depositing requisite EMD as specified in the "Schedule".
- 12. Copy of all mandatory documents as desired in the NIT shall be scanned and up-loaded to the e-Tendering website within the period of bid submission. However, certified / original copy of all the scanned and up-loaded documents shall have to be submitted by the lowest bidder only within a week physically in the office of e-tendering authority.

Page 9 of 64



- **13.** Online bid documents submitted by intending bidders shall be opened only of those bidders, who has deposited requisite EMD / attached scanned copy and other documents scanned and uploaded are found in order.
- **14.** Those contractors not registered on the website mentioned above, are required to get registered beforehand. Bidders should refer "Instruction for Online Bid Submission" given earlier for further assistance.
- 15. When bids are invited in two / three stages systems and if it is desired to submit revised financial bid it shall be mandatory to submit revised financial bid. If not submitted then the bid submitted earlier shall become invalid.
- **16.** The department reserves the right to reject any prospective application without assigning any reason and to restrict the list of qualified contractors to any number deemed suitable by it, if too many bids are received satisfying the laid down criterion.
- **17.** Contractors must ensure to quote rate of each item.
- **18.** The Lift Manufacturer shall comply with BIS standards, duly certified by designated labs / certifying agencies.
- **19.** The manufacturer shall be complaint to the Public Procurement (Preference to Make in India), Order 2017 (as amended from time to time) issued by the Department of Industrial Policy and Promotion(DIPP), Ministry of Commerce and Industry.
- **20.** The experience of successful completion of similar works shall be as per CPWD Works Manual/SoP.
- **21.** The Manufacturer shall furnish an undertaking regarding availability of spares for the entire life of the lift i.e. 15 to 20 years.
- 22. The complete Lift installation including its components, safety device, various types of controls etc., testing, inspection, operation & maintenance shall conform to relevant Codes / Standard /Code of practices / Guidelines / Safety Rules / Inspection Manual (s) / Rule issued by Bureau of Indian Standards, as amended upto date..
- 23. Quality Standards shall conform to IS/ISO-9001:2015 as amended.
- 24. The Down Time of installed lifts, which are being maintained by the manufacturer, shall not be more than 8 hours (average) in case of minor faults and 7 days (average) in case of major faults in last one year. The data to be considered shall be for last financial year.
- **25.** The eligible tenderers quote rates for various items of major components of work. The lowest tenderer is decided based on the quoted rates in respect of all schedules attached in tender documents. It is obligatory on the part of the main contractor to sign the tender document for all the components.

Page **10** of **64**



List of Mandatory Documents to be scanned and uploaded within the period of bid submission:

- Annexure I duly filled in and duly mentioning UTR No. for EMD deposition or Banker's Cheque or Demand Draft or FDR number with date of issue and got signed
- 2. Proof of EMD deposit / Scanned copy of DD submission (favouring 'Registrar, IIT Delhi').

 The following undertaking on firm's letter head shall be uploaded by the bidder I scanned copy of DD/FDR is uploaded by the bidder: "The exact physical EMD (as uploaded) shall be deposited by me / us with the authority inviting tender, in case I/we become the lowest tenderer, within a week of the opening of financial bid, otherwise, IITD may reject the tender and also take actions to debar me/ us from tendering in any form in IIT Delhi".
- 3. Certificate of work experience as desired (vide clause 4 above)
- 4. Certificate of GST Registration of the State in which the work is to be taken up, if already obtained by the bidder. If the bidder has not obtained GST registration in the State in which the work is to be taken up, or as required by GST authorities then in such a case the bidder shall scan and upload following undertaking alongwith other bid documents.

"if work is awarded to me, I/we shall obtain GST registration certificate of the State, in which work is to be taken up within one month from the date of receipt of award letter or before release of any payment by IIT Delhi, whichever is earlier, failing which I/we shall be responsible for any delay in payments which will be due towards me/us on a/c of the work executed and/or for any action taken by IIT Delhi or GST department in this regard."

- 5. Affidavit as per provision of the clause 1.1.2 of IITD-6 [To be submitted on stamp paper]
- 6. Acceptance to execute INTEGRITY PACT [see integrity pact]
- 7. IITD 7 / 8 duly signed
- EPFO & ESIC Registration proof
- 9. Valid Electrical Licence- Not Mandatory for OEM
- 10. Technical Compliance sheet (Annexure H) duly filled in and signed with Annexure X1 & X2 on OEM Letter Head along with manufacturing, servicing and performance certification required.
- 11. Certificate (that the OEM is complying with BIS standards) duly certified by designated labs / certifying agencies.
- 12. Certificate in this regard that the OEM is PPP MII Order-2017 (as amended) compliant.
- 13. An undertaking on OEM letter head regarding availability of spares for the entire life of the lift
- 14. Quality Standards certificates of OEM conforming to IS/ISO-9001:2015 (as amended)

Page 11 of 64



- 15. Certificate on OEM letter head that the complete Lift installation including its components, safety device, various types of controls etc., testing, inspection, operation & maintenance shall conform to relevant Codes / Standard /Code of practices / Guidelines / Safety Rules / Inspection Manual (s) / Rule issued by Bureau of Indian Standards, as amended upto date.
- 16. "The Down Time of installed lifts (mentioning details of capacity of lifts, date of commissioning, etc.), which are being maintained by the manufacturer, shall not be more than 8 hours (average) in case of minor faults and 7 days (average) in case of major faults in last one year. The data to be considered shall be for last financial year." A certificate in this regard from the present client of OEM shall have to be enclosed with Technical bid.
- 17. Any other document as specified in the NIT

[N.B. -- As per CPWD Works Manual 2019, "MSME firms registered in NSIC under PP policy are exempted from payment of EMD for supply of goods and services only" Hence, there is **no applicability of EMD exemption** for this work. BID without EMD will summarily be rejected]

Executive Engineer [ED-I] For & on Behalf of BOG, IIT Delhi

Page 12 of 64

IITD - 6

INDIAN INSTITUTE OF TECHNOLOGY DELHI

NOTICE INVITING E-TENDER

- 1.0 Item rate tenders are invited on behalf of The Board of Governors, IIT Delhi, Hauz Khas, New Delhi 110016 from "CPWD, MES, BSNL, Railways Enlisted Contractors of Composite Category in appropriate class and specialized agency" as per details given below for the work of Replacement of 5 x 8 Passenger Lifts at different places in IIT Delhi.
- 1.1 The work is estimated to cost Rs.1,06,07,941.00. This estimate, however, is given merely as a rough guide.
- 1.1.1 Criteria of eligibility for submission of bid documents: Conditions for intending bidders / contractors:
- 1.1.1.1 Three similar works each costing not less than Rs. 42,44,000.00, or two similar works each costing not less than Rs.63,65,000.00, or one similar work costing not less than Rs.84,87,000.00 in last 7 years ending previous day of last date of submission of bids. The value of executed work shall be brought to current costing level by enhancing the actual value of work at simple rate of 7% per annum; calculated from the date of completion to last date of submission of financial bid.
- 1.1.2 To become eligible for issue of bid, the bidders shall have to furnish an affidavit as under:

 "I / We undertake and confirm that eligible similar works(s) has/have not been got executed through another contractor on back to back basis. Further that, if such a violation comes to the notice of Department, then I / we shall be debarred for bidding in IIT Delhi in future forever. Also, if such a violation comes to the notice of Department before date of start of work, the Engineer-in-Charge shall be free to forfeit the entire amount of Earnest Money Deposit/Performance Guarantee (Scanned copy to be uploaded at the time of submission of bid)".
- Agreement shall be drawn with the successful bidders on prescribed Form No. IITD 7/8 which is available as IIT Delhi Publication. Bidders shall quote their rates as per various terms and conditions of the said form which will form part of the agreement.
- 3.0 The time allowed for carrying out the work will be 270 days from the date of start as defined in schedule 'F' or from the first date of handing over of the site, whichever is later, in accordance with the phasing, if any, indicated in the bid documents.
- **4.0** The site for the work is available.
- The bid document consisting of plans, specifications, the schedule of quantities of various types of items to be executed and the set of terms and conditions of the contract to be complied with and other necessary documents except Standard General Conditions of Contract Form can be seen from the web Site **e-procure.gov.in.**
- After submission of the bid the contractor can re-submit revised bid any number of times but before last time and date of submission of tender as notified.
- **7.0** While submitting the revised bid, contractor can revise the rate of one or more item(s) any number of times (he need not re-enter rate of all the items) but before last time and date of submission of tender as notified.
- 8.0 If it is desired to submit revised financial bid then it shall be mandatory to submit revised financial bid. If not submitted then the tender submitted earlier shall become invalid.
- 9.0 Earnest Money as specified to be paid through RTGS / NEFT. IIT Delhi Bank details are as under: Name of the Bank A/C: IITD Revenue Account; SBI A/C No.: 10773572622; Name of the Bank: State Bank of India, IIT Delhi, Hauz Khas, New Delhi-110016; IFSC Code: SBIN0001077; MICR Code: 110002156; Swift No.: SBININBB547 (This is mandatory that UTR Number is provided in the on-line quotation/bid. Kindly refer to the UTR Column of the Declaration Sheet at Annexure-1). OR In the form of Banker's Cheque or Demand Draft or FDR of scheduled bank in favour of Registrar, IIT Delhi (scanned copy of the same to be uploaded with the bid,

Page **13** of **64**



and to ear.

date of issue shall be within the NIT period) Interested contractor who wish to participate in the bid has to ensure payment of EMD within the period of bid submission.

- 9.1 Copy of all 'mandatory documents' and other documents as specified in the press notice shall be scanned and uploaded to the e-tendering website within the period of bid submission. However, certified copy of all the scanned and uploaded documents alongwith original EMD (of scanned copy) as specified in press notice shall have to be submitted by the lowest bidder only within a week physically in the office of tender opening authority.
- **10.0** The bid submitted shall become invalid, if:
- **10.1** The bidder is found ineligible.
- 10.2 The bidder does not upload all the documents (including GSTIN Registration) as stipulated in the bid document.
- **10.3** EMD not deposited online or not submitted as specified
- 10.4 If any discrepancy is noticed between the documents as uploaded at the time of submission of bid and hard copies as submitted *physically by the lowest bidder* in the office of the bid opening authority.
- The contractor whose bid is accepted will be required to furnish performance guarantee of 5% (Five Percent) of the bid amount within the period specified in Schedule F. This guarantee shall be in the form of Deposit at Call receipt of any scheduled bank / Banker' cheque of any scheduled bank/ Demand Draft of any scheduled bank/Pay order of any Scheduled Bank (in case guarantee amount is less than Rs.1,00,000/-) or Government Securities or Fixed Deposit Receipts or irrevocable Bank Guarantee Bonds of any Scheduled Bank or the State Bank of India in accordance with the prescribed form. In case the contractor fails to deposit the said performance guarantee within the period as indicated in Schedule 'F' including the extended period if any, the Earnest Money deposited by the contractor shall be forfeited automatically without any notice to the contractor. The earnest money deposited alongwith bid shall be returned after receiving the aforesaid performance guarantee.
- Intending Bidders are advised to inspect and examine the site and its surroundings and satisfy themselves before submitting their bids as to the nature of the ground and subsoil (so far as is practicable), the form and nature of the site, the means of access to the site, the accommodation they may require and in general shall themselves obtain all necessary information as to risks, contingencies and other circumstances which may influence or affect their bid. A bidder shall be deemed to have full knowledge of the site whether he inspects it or not and no extra charge consequent on any misunderstanding or otherwise shall be allowed. The bidders shall be responsible for arranging and maintaining at his own cost all materials, tools & plants, water, electricity access, facilities for workers and all other services required for executing the work unless otherwise specifically provided for in the contract documents. Submission of a bid by a bidder implies that he has read this notice and all other contract documents and has made himself aware of the scope and specifications of the work to be done and of conditions and rates at which stores, tools and plant, etc. will be issued to him by the Government and local conditions and other factors having a bearing on the execution of the work.
- The competent authority on behalf of the Board of Governors does not bind itself to accept the lowest or any other bid and reserves to itself the authority to reject any or all the bids received without the assignment of any reason. All bids in which any of the prescribed condition is not fulfilled or any condition including that of conditional rebate is put forth by the bidder shall be summarily rejected.
- 14.0 Canvassing whether directly or indirectly, in connection with bidders is strictly prohibited and the bids submitted by the contractors who resort to canvassing will be liable for rejection.
- The competent authority on behalf of the Board of Governors reserves to himself the right of accepting the whole or any part of the bid and the bidder shall be bound to perform the same at the rate quoted.

Page **14** of **64**



~ 9 p av

- The contractor shall not be permitted to bid for works in the IITD responsible for award and execution of contracts, in which his near relative is posted a Divisional Accountant or as an officer in any capacity between the grades of Superintending Engineer and Junior Engineer (both inclusive). He shall also intimate the names of persons who are working with him in any capacity or are subsequently employed by him and who are near relatives to any Gazetted officer in the IIT Delhi. Any breach of this condition by the contractor would render him liable to be debarred from bidding process in future in IIT Delhi.
- No Engineer of Gazetted rank or other Gazetted Officer employed in Engineering or Administrative duties in an Engineering Department of the Government of India is allowed to work as a contractor for a period of one year after his retirement from Government service, without the prior permission of the Government of India in writing. This contract liable to be cancelled, if, either the contractor or any of his employees is found any time to be such a person who had not obtained the permission of the Government of India as aforesaid before submission of the bid or engagement in the contractor's service.
- The bid for the works shall remain open for acceptance for a period of **ninety days from the date**of opening of financial bids, if any bidder withdraws his bid before the said period or issue of
 letter of acceptance, whichever is earlier, or makes any modifications in the terms and conditions
 of the bid which are not acceptable to the department, then the IIT Delhi shall, without prejudice
 to any other right or remedy, be at liberty to forfeit 50% of the said earnest money as aforesaid.
 Further the bidder shall not be allowed to participate in the re-bidding process of the work.
- 19.0 This notice inviting bid shall form a part of the contract document. The successful bidder / contractor, on acceptance of his bid by the Accepting Authority shall within fifteen days from the stipulated date of start of the work, sign the contract consisting of:-
- The Notice Inviting Bid, all the documents including additional conditions, specifications and drawings, if any, forming part of the bid as uploaded at the time of invitation of bid and the rates quoted online at the time of submission of bid and acceptance thereof together with any correspondence leading thereto.
- 19.2 Standard IITD Form –7/8 or other Standard IITD Form as applicable.
- In case any discrepancy is noticed between the documents as uploaded at the time of submission of the bid online and hard copies as to be submitted physically in IIT Delhi, if so desired by the tender inviting authority, then the bid submitted shall become invalid and the IIT Delhi shall, without prejudice to any other right or remedy, be at liberty to forfeit 50% of the said earnest money as aforesaid. Further the bidder shall not be allowed to participate in the bidding process of the work.
- GST or any other taxes applicable in respect of inputs procured by the contractor for this contract shall be payable by the contractor and government will not entertain any claim whatsoever in respect of the same. However, component of GST at the time of supply of service (as provided in CGST Act 2017) provided by the contractor shall be varied if different from the applicable on the last date of receipt of tender including extension of any.
- 22.0 Undertaking regarding submission of EMD or original document within 7 days by lowest Bidder from opening of financial bid.

Page 15 of 64



INTEGRITY PACT

То
Sub: NIT No. 0276/121/IITD/EW/2023-24 for the work of "Replacement of 5 x 8 Passenger Lifts at different places in IIT Delhi."
Dear Sir,
It is hereby declared that IIT Delhi (IITD) is committed to follow the principle of transparency, equity and competitiveness in public procurement.
The subject Notice Inviting Tender (NIT) is an invitation to offer made on the condition that the Bidder will sign the Integrity Agreement, which is an integral part of the tender/bid documents, failing which the tender/bidder will stand disqualified from the tendering process and the bid of the bidder would be summarily rejected.
This declaration shall form part and parcel of the Integrity Agreement and signing of the same shall be deemed as acceptance and signing of the Integrity Agreement on behalf of the IITD.
Yours faithfully,
Executive Engineer[ED-I]

Page **16** of **64**

 $C \ldots Nil \quad I \ldots \ldots Nil \quad O \ldots \ldots Nil$



[TO BE SUBMITTED DULY SIGNED BY THE BIDDER ALONGWITH BID DOCUMENTS]

To

Executive Engineer (ED-I), IIT Delhi, Hauz Khas, New Delhi – 110016

Subject: Submission of Bid for the work of "Replacement of 5 x 8 Passenger Lifts at different places in IIT Delhi."

Dear Sir,

I / We acknowledge that IIT Delhi is committed to follow the principles thereof as enumerated in the Integrity Agreement enclosed with the tender/bid document.

I / We agree that the Notice Inviting Tender (NIT) is an invitation to offer made on the condition that I / We will sign the enclosed integrity Agreement, which is an integral part of tender / bid documents, failing which I / We will stand disqualified from the tendering process. I / We acknowledge that THE MAKING OF THE BID SHALL BE REGARDED AS AN UNCONDITIONAL AND ABSOLUTE ACCEPTANCE of this condition of the NIT.

I / We confirm acceptance and compliance with the Integrity Agreement in letter and spirit and further agree that execution of the said Integrity Agreement shall be separate and distinct from the main contract, which will come into existence when tender/bid is finally accepted by IITD. I / We acknowledge and accept the duration of the Integrity Agreement, which shall be in the line with Article 1 of the enclosed Integrity Agreement.

I / We acknowledge that in the event of my/our failure to sign and accept the Integrity Agreement, while submitting the tender/bid, IITD shall have unqualified, absolute and unfettered right to disqualify the tenderer /bidder and reject the tender/bid is accordance with terms and conditions of the tender/bid.

Yours faithfully,

(Duly signed by authorized signatory of the Bidder)

Page 17 of 64

[To be signed by the bidder and same signatory competent / authorized to sign the relevant contract on behalf of IITD]

INTEGRITY AGREEMENT

This Integrity Agreement is made at on this day of
BETWEEN
The Board of Governors, IIT Delhi, Hauz Khas, New Delhi - 16 represented through Executive Engineer (ED-I), IIT Delhi
referred as the 'Principal/Owner',
AND
(Name and Address of the Individual/firm/Company) Through
<u>PREAMBLE</u>
WHEREAS the Principal / Owner has floated the Tender (NIT No. 0276/121/IITD/EW/2023-24) (hereinafter referred to as "Tender/Bid") and intends to award, under laid down organizational procedure, contract for "Replacement of 5 x 8 Passenger Lifts at different places in IIT Delhi." (Name of work) hereinafter referred to as the "Contract".
AND WHEREAS the Principal/Owner values full compliance with all relevant laws of the land, rules, regulations, economic use of resources and of fairness/transparency in its relation with its Bidder(s) and Contractor(s) AND WHEREAS to meet the purpose aforesaid both the parties have agreed to enter into this Integrity Agreement (hereinafter referred to as "Integrity Pact" or "Pact"), the terms and conditions of which shall also be read as integral part and parcel of the Tender/Bid documents and Contract between the parties.
NOW, THEREFORE, in consideration of mutual covenants contained in this Pact, the parties hereby agree as follows and this Pact witnesses as under:
Page 18 of 64 C Nil I Nil O Nil

Tender Document for Replacement of 5 x 8 Passenger Lifts at different places in IIT Delhi.

ARTICLE 1: COMMITMENT OF THE PRINCIPAL / OWNER

- **1.** The Principal/Owner commits itself to take all measures necessary to prevent corruption and to observe the following principles:
 - **1.1.** No employee of the Principal / Owner, personally or through any of his / her family members, will in connection with the Tender, or the execution of the Contract, demand, take a promise for or accept, for self or third person, any material or immaterial benefit which the person is not legally entitled to.
 - **1.1.1.** The Principal/Owner will, during the Tender process, treat all Bidder(s) with equity and reason. The Principal/Owner will, in particular, before and during the Tender process, provide to all Bidder(s) the same information and will not provide to any Bidder(s) confidential / additional information through which the Bidder(s) could obtain an advantage in relation to the Tender process or the Contract execution.
 - **1.1.2.** The Principal/Owner shall Endeavour to exclude from the Tender process any person, whose conduct in the past has been of biased nature.
- 2. If the Principal/Owner obtains information on the conduct of any of its employees which is a criminal offence under the Indian Penal code (IPC)/Prevention of Corruption Act, 1988 (PoC Act) or is in violation of the principles herein mentioned or if there be a substantive suspicion in this regard, the Principal/Owner will inform the Chief Vigilance Officer and in addition can also initiate disciplinary actions as per its internal laid down policies and procedures.

ARTICLE 2: COMMITMENT OF THE BIDDER(S) / CONTRACTOR(S)

- 1. It is required that each Bidder/Contractor (including their respective officers, employees and agents) adhere to the highest ethical standards, and report to the Government / Department all suspected acts of **fraud or corruption or coercion or collusion** of which it has knowledge or becomes aware, during the tendering process and throughout the negotiation or award of a contract.
- 2. The Bidder(s)/Contractor(s) commits himself to take all measures necessary to prevent corruption. He commits himself to observe the following principles during his participation in the Tender process and during the Contract execution:
 - 2.1. The Bidder(s)/Contractor(s) will not, directly or through any other person or firm, offer, promise or give to any of the Principal/Owner's employees involved in the Tender process or execution of the Contract or to any third person any material or other benefit which he/she is not legally entitled to, in order to obtain in exchange any advantage of any kind whatsoever during the Tender process or during the execution of the Contract.
 - **2.2.** The Bidder(s)/Contractor(s) will not enter with other Bidder(s) into any undisclosed agreement or understanding, whether formal or informal. This applies in particular to prices, specifications, certifications, subsidiary contracts, submission or non-submission of bids or any other actions to restrict competitiveness or to cartelize in the bidding process.
 - 2.3. The Bidder(s) / Contractor(s) will not commit any offence under the relevant IPC/PoC Act. Further the Bidder(s) / Contractor(s) will not use improperly, (for the purpose of competition or personal gain), or pass on to others, any information or documents provided by the Principal / Owner as part of the business relationship, regarding plans, technical proposals and business details, including information contained or transmitted electronically.
 - **2.4.** The Bidder(s) / Contractor(s) of foreign origin shall disclose the names and addresses of agents / representatives in India, if any. Similarly Bidder(s) / Contractor(s) of Indian Nationality shall disclose names and addresses of foreign agents/representatives, if any. Either the Indian agent

Page **19** of **64**



on behalf of the foreign principal or the foreign principal directly could bid in a tender but not both. Further, in cases where an agent participate in a tender on behalf of one manufacturer, he shall not be allowed to quote on behalf of another manufacturer along with the first manufacturer in a subsequent/parallel tender for the same item.

- **2.5.** The Bidder(s)/Contractor(s) will, when presenting his bid, disclose any and all payments he has made, is committed to or intends to make to agents, brokers or any other intermediaries in connection with the award of the Contract.
- **3.** The Bidder(s)/Contractor(s) will not instigate third persons to commit offences outlined above or be an accessory to such offences.
- 4. The Bidder(s)/Contractor(s) will not, directly or through any other person or firm indulge in fraudulent practices means a wilful misrepresentation or omission of facts or submission of fake/forged documents in order to induce public official to act in reliance thereof, with the purpose of obtaining unjust advantage by or causing damage to justified interest of others and/or to influence the procurement process to the detriment of the Government interests.
- 5. The Bidder(s)/Contractor(s) will not, directly or through any other person or firm use Coercive Practices (means the act of obtaining something, compelling an action or influencing a decision through intimidation, threat or the use of force directly or indirectly, where potential or actual injury may befall upon a person, his/ her reputation or property to influence their participation in the tendering process).

ARTICLE 3: CONSEQUENCES OF BREACH

Without prejudice to any rights that may be available to the Principal / Owner under law or the Contract or its established policies and laid down procedures, the Principal/Owner shall have the following rights in case of breach of this Integrity Pact by the Bidder(s)/Contractor(s) and the Bidder/ Contractor accepts and undertakes to respect and uphold the Principal/Owner's absolute right:

- 1. If the Bidder(s)/Contractor(s), either before award or during execution of Contract has committed a transgression through a violation of Article 2 above or in any other form, such as to put his reliability or credibility in question, the Principal/Owner after giving 14 days' notice to the contractor shall have powers to disqualify the Bidder(s)/Contractor(s) from the Tender process or terminate/determine the Contract, if already executed or exclude the Bidder/Contractor from future contract award processes. The imposition and duration of the exclusion will be determined by the severity of transgression and determined by the Principal/Owner. Such exclusion may be forever or for a limited period as decided by the Principal/Owner.
- 2. Forfeiture of EMD/Performance Guarantee/Security Deposit: If the Principal/Owner has disqualified the Bidder(s) from the Tender process prior to the award of the Contract or terminated/determined the Contract or has accrued the right to terminate/determine the Contract according to Article 3(1), the Principal/Owner apart from exercising any legal rights that may have accrued to the Principal/Owner, may in its considered opinion forfeit the entire amount of Earnest Money Deposit, Performance Guarantee and Security Deposit of the Bidder/Contractor.
- 3. Criminal Liability: If the Principal/Owner obtains knowledge of conduct a Bidder or Contractor, or of an employee or a representative or an associate of a Bidder or Contractor which constitutes corruption within the meaning of IPC Act, or if the Principal / Owner has substantive suspicion in this regard, the Principal/Owner will inform the same to law enforcing agencies for further investigation.

ARTICLE 4: PREVIOUS TRANSGRESSION

Page 20 of 64



- 1. The Bidder declares that no previous transgressions occurred in the last 5 years with any other Company in any country confirming to the anticorruption approach or with Central Government or State Government or any other Central/State Public Sector Enterprises in India that could justify his exclusion from the Tender process.
- 2. If the Bidder makes incorrect statement on this subject, he can be disqualified from the Tender process or action can be taken for banning of business dealings/ holiday listing of the Bidder/Contractor as deemed fit by the Principal/ Owner.
- 3. If the Bidder/Contractor can prove that he has resorted / recouped the damage caused by him and has installed a suitable corruption prevention system, the Principal/Owner may, at its own discretion, revoke the exclusion prematurely.

ARTICLE 5: EQUAL TREATMENT OF ALL BIDDERS/CONTRACTORS/SUBCONTRACTORS

- 1. The Bidder(s)/Contractor(s) undertake(s) to demand from all subcontractors a commitment in conformity with this Integrity Pact. The Bidder/Contractor shall be responsible for any violation(s) of the principles laid down in this agreement/Pact by any of its Sub-contractors/sub-vendors.
- 2. The Principal/Owner will enter into Pacts on identical terms as this one with all Bidders and Contractors.
- **3.** The Principal/Owner will disqualify Bidders, who do not submit, the duly signed Pact between the Principal/Owner and the bidder, along with the Tender or violate its provisions at any stage of the Tender process, from the Tender process.

ARTICLE 6: DURATION OF THE PACT


- 1. This Pact begins when both the parties have legally signed it. It expires for the Contractor/Vendor 6 months after the completion of work under the contract or till the continuation of defect liability period, whichever is more and for all other bidders, till the Contract has been awarded.
- 2. If any claim is made/lodged during the time, the same shall be binding and continue to be valid despite the lapse of this Pacts as specified above, unless it is discharged/determined by the Competent Authority of IIT Delhi.

ARTICLE 7: OTHER PROVISIONS

- **1.** This Pact is subject to Indian Law, place of performance and jurisdiction is the Head Quarters of the Division of the Principal/Owner, who has floated the Tender.
- 2. Changes and supplements need to be made in writing. Side agreements have not been made.
- 3. If the Contractor is a partnership or a consortium, this Pact must be signed by all the partners or by one or more partner holding power of attorney signed by all partners and consortium members. In case of a Company, the Pact must be signed by a representative duly authorized by Board Resolution.
- **4.** Should one or several provisions of this Pact turn out to be invalid; the remainder of this Pact remains valid. In this case, the parties will strive to come to an agreement to their original intensions.
- 5. It is agreed term and condition that any dispute or difference arising between the parties with regard to the terms of this Integrity Agreement / Pact, any action taken by the Owner/Principal in accordance with this Integrity Agreement / Pact or interpretation thereof shall not be subject to arbitration.

ARTICLE 8: LEGAL AND PRIOR RIGHTS

Page **21** of **64**





****3 to e[®]!"

1. All rights and remedies of the parties hereto shall be in addition to all the other legal rights and remedies belonging to such parties under the Contract and/or law and the same shall be deemed to be cumulative and not alternative to such legal rights and remedies aforesaid. For the sake of brevity, both the Parties agree that this Integrity Pact will have precedence over the Tender/Contact documents with regard any of the provisions covered under this Integrity Pact.

IN WITNESS WHEREOF the parties have signed and executed this Integrity Pact at the place and date first above mentioned in the presence of following witnesses:

(For and on behalf of Principal / Owner)
(For and on behalf of Bidder / Contractor)
WITNESSES:
1
(signature, name and address)
2(signature, name and address)
Place:
Dated :

Page 22 of 64

IITD - 7/8

INDIAN INSTITUTE OF TECHNOLOGY DELHI

HAUZ KHAS, NEW DELHI - 110016

Percentage Rate Tender / Item Rate Tender & Contract for Works

Tender for the work of "Replacement of 5 x 8 Passenger Lifts at different places in IIT Delhi."

- 1. To be submitted online by Upto 03.00 PM of 29.05.2024
- 2. To be opened on 30.05.2024 at 03.00 PM online

e-TENDER

I / We have read and examined the Notice Inviting Tender, schedule, A, B, C, D, E & F, Specifications applicable, Drawings & Designs, General Rules and Directions, Conditions of Contract, Clauses of Contract, Special conditions, Schedule of Rate & other documents and Rules referred to in the conditions of contract and all other contents in the tender document for the work.

I / We hereby tender for the execution of the work specified for the Board of Governors, IIT Delhi within the time specified in Schedule 'F' viz., schedule of quantities and in accordance in all respect with the specifications, designs, drawing and instructions in writing referred to in Rule-1 of General Rules and Directions and in Clause 11 of the Conditions of contract and with such materials as are provided for, by, and in respect of accordance with, such conditions so far as applicable.

We agree to keep the tender open for ninety (90) days from the due date of its opening / ninety days from the date of opening of financial bid in case tenders are invited on 2/3 envelop system (**strike out as the case may be**) and not to make any modification in its terms and conditions.

A sum of Rs.2,12,159.00 is hereby deposited in IIT Delhi Revenue Account No. 10773572622 as earnest money / D.D. for Rs. 2,12,159.00 has been uploaded with bid. (Strike out whichever is applicable. If I / We, fail to furnish the prescribed performance guarantee within prescribed period I / We agree that the said The Board of Governors, IIT Delhi, Hauz Khas, New Delhi - 16 or his successors, in office shall without prejudice to any other right or remedy, be at liberty to forfeit the said earnest money absolutely. Further, if I / We fail to commence the work as specified, I / We agree that The Board of Governors, IIT Delhi, Hauz Khas, New Delhi - 16 or the successors in office shall without prejudice to any other right or remedy available in law, be at liberty to forfeit the said earnest money and the performance guarantee absolutely, otherwise the said earnest money shall be retained by him towards security deposit to execute all the works referred to in the tender documents upon the terms and conditions contained or referred to those in excess of that limit at the rates to be determined in accordance with the provision contained in Clause 12.2 and 12.3 of the tender form. Further, I / We agree that in case of forfeiture of Earnest Money & Performance Guarantee as aforesaid I / We shall be debarred for participation in the re-tendering process of the work.

I / We undertake and confirm that eligible similar work(s) has/have not been got executed through another contractor on back to back basis. Further that, if such a violation comes to the notice of Department, then I / We shall be debarred for tendering in IIT Delhi in future forever. Also, if such a violation comes to the notice of Department before date of start of work, the Engineer-in-Charge shall

Page 23 of 64



Tender Document for Replacement of 5 x 8 Passenger Lifts at different places in IIT Delhi.

be free to forfeit the entire amount of Earnest Money Deposit/Performance Guarantee.

I / We hereby declare that I / We shall treat the tender documents drawings and other records connected with the work as secret/confidential documents and shall not communicate information/derived there from to any person other than a person to whom I / We am/are authorized to communicate the same or use the information in any manner prejudicial to the safety of the State.

Dated:	
	Signature of Contractor
Witness:	
Address:	Postal Address
Occupation:	
	ACCEPTANCE
accepted by me for an on behalf of The Board	you as provided in the letters mentioned hereunder) is d of Governors, IIT Delhi, Hauz Khas, New Delhi - 110016) In part of this contract agreement:-
(a)	
(b)	
(c)	
	For & on behalf of Board of Governors, IIT Delhi
	Signature
Dated:	Designation

Page 24 of 64



PROFORMA OF SCHEDULES

SCHEDULE "A"

Schedule of Quantities (enclosed)

SCHEDULE "B"

Schedule of materials to be issued to the contractor

Sr. No.	Description of item	Quantity	Rates in figures & words at which the materials will be charged from the contractor	Place of issue
(1)	(2)	(3)	(4)	(5)
	NIL			

SCHEDULE "C"

Tools and Plants to be hired to the contractor

Sr. No.	Description	Hire charges per day	Place of issue
(1)	(2)	(3)	(4)
	NIL		

SCHEDULE "D"

Extra schedule for specific requirements / documents for the work, if any.



SCHEDULE "E"

Reference to General Conditions of Contract

1	Reference to general conditions of Contract	:	GCC for maintenance work 2023 for CPWD work along with correction slip / amendment issued upto last date of submission of bid.
2	Name of work	:	Replacement of 5 x 8 Passenger Lifts at different places in IIT Delhi.
3	Estimated cost of work (Rs.)		1,06,07,941.00
4	Earnest Money (Rs.)	:	2,12,159.00

Page 25 of 64



5	Performance Guarantee	:	5 percent of tendered value
6	Security Deposit	:	2.5 percent of tendered value

SCHEDULE "F"

GENERAL RULES & DIRECTIONS:

Officer inviting tender	••	Executive Engineer (ED-I)
Maximum percentage for quantity of items of		See below
work to be executed beyond which rates are to		
be determined in accordance with Clauses 12.2		
& 12.3		

DEFINITIONS:

2 (V)	Engineer-in-charge	••	Executive Engineer (ED-I)				
2 (viii)	Accepting authority	••	Institute Engineer				
2 (x)	Percentage on cost of materials and labour to cover all overheads and profits	:	20 percent				
2 (xi)	Standard Schedule of Rates		Market, DSR & PAR of CPWD				
2 (xii)	Department	:	Estate & Works, IIT Delhi				
9 (ii)	Reference to General condition of contract	:	GCC for maintenance work 2023 for CPWD works along with correction on slips/amendment issued up to last date of Submission of bid.				

CLAUSE 1

i)	Time allowed for submission of Performance Guarantee from the date of issue of letter of acceptance	:	15 days
ii)	Maximum allowable extension beyond the period provided in (i) above with late fees @0.1% per day of performance guarantee		10 days

CLAUSE 2

(i)	Authority for fixing compensation	:	Institute Engineer
	under Clause 2		

Page **26** of **64**



CLAUSE 2A

(i)	Whether	Clause	2A	shall	be	:	No
	applicable						

CLAUSE 5

(i)	Number of days from the date of	:	10 days
	issue of letter of acceptance for		
	reckoning date of start		

TABLE OF MILE STONE(S):

Sr. No.	Description of Milestone (physical)	Time allowed in days (from date of start)	Amount to be with-held in case of non-achievement of milestone
(1)	(2)	(3)	(4)
1	1/8 th (of the whole work)	1/4 th (of whole work)	1% of tendered value of work
2	3/8 th (of whole work)	1/2 nd (of whole work)	1% of tendered value of work
3	3/4 th (of whole work)	3/4 th (of whole work)	1% of tendered value of work
4	Full	Full	1% of tendered value of work

Time allowed for execution of work	:	270 days

Authority to	Extension of time	:	Engineer-in-charge
decide:	Rescheduling of milestones	:	Institute Engineer

CLAUSE 6A

Clause applicable – (6A)	: 6 A

CLAUSE 7

Gross	work	to	be	done	together	with	net	payment	/	:	
adjustr	nent of	ad	vanc	es for	materials	collec	ted, i	if any, since	Э		20 Lakhs
the las	t such	pay	men	t for be	eing eligibl	le to ir	nterin	n payment			

Page **27** of **64**

CLAUSE 10A

	List of testing equipment to be provided by the contractor at site lab								
1	NIL	2	NIL	3	NIL				
4	NIL	5	NIL	6	NIL				

CLAUSE 10B (ii)

Whether Clause 10 B (ii) shall be applicable (Yes /	:	No
No)		

CLAUSE 10 C

Component of labour expressed as percent of value of	:	15 Percent
work		

CLAUSE 10 CA (Not Applicable)

Ma	aterials covered	Nearest materials (other than cement,	Base Price of all the
under this clause		reinforcement bars & structural steel) for	
		which All India Wholesale Price index to be	under clause 10 CA*
		followed	
1	NIL		
2	NIL		
3	NIL		
4	NIL		

^{*}base price of all materials covered under clause 10 CA is to be mentioned at the time of approval of NIT

CLAUSE 10CC (Not Applicable)

Clause 10 CC to be applicable in contracts with stipulated period of completion exceeding the period shown in next column	:	00 months
Schedule of component of other Materials, Labour, P.O.L. etc. for price escalation.		
Component of Civil (except materials covered under clause 10 CA) / Electrical construction materials - expressed as percent of total value of work	:	X _m = percent
Component of labour - expressed as percent of total value of work	:	Y = percent
Component of P.O.L. – expressed as percent of total value of work	:	Z= percent

Page 28 of 64

Tender Document for Replacement of 5 x 8 Passenger Lifts at different places in IIT Delhi.

CLAUSE 11

Specification to	be	followed	for	:	CPWD	General	Specifications	for	Electric	cal
execution of work					Works	(Part III	Lift & Escalat	or)	and oth	ner
					relevant Parts as amended upto date					

CLAUSE 12

12.2 & 12.3	Deviation limit beyond which clauses 12.2 & 12.3 shall apply for building work	:	100%
12.3 A	Type of work		Maintenance works including works of up-gradation, aesthetic, special repair, addition / alteration
12.5	Deviation limit beyond which clauses 12.2 & 12.3 shall apply for foundation work	:	100%

CLAUSE 16

Competent authority for deciding reduced rates	:	Executive Engineer
Competent admitsing for accounting	-	_,g

CLAUSE 18

	List of mandatory machinery, tools & plants to be deployed by the contractor at site							
1	NIL	2	NIL	3	NIL			
4	NIL	5	NIL	6	NIL			

CLAUSE 32

Requirement of Technical Representative (s) and recovery rate

Sr. No.	Minimum qualification of Technical Representative	Discipline	Designation Principal Technical / Technical representative)	Minimum experience	Number	shall be m contractor i not fulfilling claus	nich recovery ade from the n the event of g provision of se 36 (i)
						Figures	Words
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)

Page 29 of 64



1	Graduate	Electrical	Technical	2 years	1	15000	Rupees
	Engineer	or	Representative	for			Fifteen
	or	Electrical		Graduate			Thousand
	Diploma	&		and 5			per month
	Engineer	Electronics		years for			per person
	-			Diploma			

Assistant Engineers retired from Govt. / IIT Delhi services that are holding Diploma will be treated at par with Graduate Engineers.

COMMERCIAL AND ADDITIONAL CONDITIONS

1. GENERAL

- 1.1. This specification covers manufacture, testing as may be necessary before dispatch, delivery at site, all preparatory work, assembly and installation, commissioning, putting into operation of Lifts & Escalators.
- **1.2.** Location: The equipments will be installed at MS Building, Vishwakarma Bhawan building, Taxila Apartment, Synergy Building at IIT Delhi
- 1.3. The work shall be executed as per CPWD General Specifications for Electrical Works Part-I (Int.) 2013, Part-II (Ext.) 1994, Part-IV (Sub St.) 2013, Part-III (Lifts & Escalators), as amended upto date, relevant I.E. Rules, BIS/IEC and as per directions of Engineer-in- Charge. These additional specifications/conditions are to be read in conjunction with above and in case of variations; specifications given in these additional conditions shall apply. However, nothing extra shall be paid on account of these additional specification and conditions, as the same are to be read along with schedule of quantities for the work.
- **1.4.** The tenderer should in his own interest visit the site and get familiarize with the site conditions before tendering.
- **1.5.** No T&P shall be issued by the Department and nothing extra shall be paid on account of this.

2. COMMERCIAL CONDITIONS:

- **2.1. Type of contract:** The work to be awarded by this tender shall be treated as **indivisible works contract.**
- 2.2. Submission and opening of Tenders:
- **2.2.1.** The tender is in two parts:
 - 2.2.1.1. Part-I -Technical cum Un-priced commercial Bid
 - 2.2.1.2. Part-II-Price Bid
- **2.3.** The tender shall be submitted online, duly completed as per NIT conditions within period of bid submission.

Page 30 of 64



and 10 agr.

- **2.4.** The tenderers are advised not to deviate from the technical specifications / item, commercial terms and conditions of NIT like terms of payment, guarantee, arbitration clause, escalation etc.
- **2.5.** Technical cum un-priced commercial bid only shall be opened on the due date and time in the presence of tenderers or their authorized representative who wish to remain present.
- 2.6. Scrutiny/evaluation of the technical-cum-commercial bid shall be done by the department. In case, it is found that the technical-cum-commercial bid of a tenderer is not in line with NIT specifications/requirements and/or contains too many deviations, the department reserves the right to reject the technical bid of such firms(s) without making any reference to the tenderer(s).
- 2.7. Necessary clarifications required by the department shall have to be furnished by the tenderer within the time given by the department for the same. The tenderer will have to depute his representative to discuss with the officer(s) of the department as and when so desired. In case, in the opinion of the department a tenderer is taking undue long time in furnishing the desired clarifications, his bid will be rejected without making any reference.
- **2.8.** After obtaining clarification from all the tenders, the department will intimate the tenders whose technical cum commercial bids are acceptable.
- 2.9. The price bids of only those tenderers shall be opened whose technical bids are found to be technically acceptable. The time and date of opening of price bid shall be fixed after the technical cum unpriced commercial bid is accepted and intimated to them by post/Fax/e-mail.
- **2.10.** The department reserves the right to reject any or all the price bids and call for fresh prices/tenders as the case may be without assigning any reason.

3. TERMS OF PAYMENTS

- 3.1. The following percentage of contact rates for the various items included in the contact shall be payable against the stage of work shown herein.
- 3.2. 80% after initial inspection and delivery at site in good condition on pro-rata basis.
- 3.3. 10% after completion of installation in all respects.
- 3.4. Balance 10% will be paid after testing, commissioning, trial run and handing over to the department for beneficial use.

4. SECURITY DEPOSIT

4.1. Security Deposit shall be deducted from each running bill and final bill to the extent of 2.5% of the gross amount payable. **The security deposit shall be released on the expiry of guarantee period stipulated in the contract**.

5. PERFORMANCE GUARANTEE

5.1. The successful tenderer shall submit an irrevocable performance guarantee of 5% of the tendered amount in addition to other deposit mentioned elsewhere in the contract for his proper performance of the contract agreement within 15 days of issue of letter of acceptance of tender. This guarantee shall be in the form of Demand Draft/Pay order of irrevocable bank guarantee bond of any schedule bank or the State Bank of India in the specified perform a of Government

Page **31** of **64**



「何ヲ」も no.lu"

Security, fixed deposit receipt pledged in favour of **Registrar**, **IIT Delhi** or as specified in the letter of acceptance of tender. The performance guarantee shall be initially valid up to the stipulated date of completion plus 60 days beyond. This bank guarantee shall be kept valid till the recording of completion certificate for the work by the competent authority.

5.2. Income tax, GST, labour cess & other statutory deduction etc. shall be made at source as per the prevalent laws. The deduction of Security Deposit, Income Tax, etc., shall be done after calculation for the above due payment as per clause 3 above and net payment shall reduce accordingly.

6. RATES

- 6.1. The rates quoted by the tenderer, shall be firm and inclusive of all taxes (including works GST & labour cess), duties, levies, etc. and all charges for packing forwarding, insurance, freight and delivery, installation, testing and commissioning etc. at site including temporary construction of storage, risks overhead charges, general liabilities/ obligations and clearance from Lift Inspector. However, the fee if any, for the inspections shall be borne by the Department.
- 6.2. The contractor has to carry out maintenance as per manufacturer's standards for a period of (1 + 5) years from the date of handing over. Nothing extra shall be paid on this account on the 1st year.
- 6.3. Reserved price for dismantled materials is fixed as indicated in BOQ. Bidder cannot quote below that rate.

7. COMPLETENESS OF TENDER

7.1. All sundry equipments, fitting, unit assemblies, accessories, hardware items, foundation bolts, termination lugs for electrical connections and all other items which are useful and necessary for efficient assembly and installation of equipment and components of the work shall be deemed to have been included in the tender irrespective of the fact whether such items are specially mentioned in the tender documents or not.

8. STORAGE AND CUSTODY OF MATERIAL

8.1. The agency has to make his own arrangement for storage. No separate storage accommodation shall be provided by the department Watch and ward of the storage and their safe custody shall be responsibility till the final taking over of the installation by the department.

9. CARE OF THE BUILDING

9.1. Care shall be taken by the contractor while handling and installing the various equipment and components of the work to avoid damage to the building. He shall be responsible for repairing all damages and restoring the same to their original finish at his cost. He shall also remove at his cost all unwanted and waste material arising out of the installation from the site of work.

10. COMPLETION PERIOD

10.1. The completion period indicated in the tender documents is for the entire work of planning, designing, approval of drawings etc, arrangement of materials & equipments, delivery at site

Page 32 of 64



including transportation, installation, testing, commissioning and handing over of the entire system to the satisfaction of the Engineer-in-charge.

11. GUARANTEE

- 11.1. All equipments shall be guaranteed for a period of 12 months from the date of taking over the installation by the department against unsatisfactory performance and / or breakdown due to defective design, workmanship or material. The equipment or component, or any part thereof, so found defective during guarantee period shall be forthwith repaired or replaced free of cost to the satisfaction of the Engineer-in- Charge. In case it is felt by the department that undue delay is being caused by the contactor in doing this, the same will be got done by the department at the risk and cost of the contractor. The decision of Engineer-in-Charge in this regard shall be final & binding on the contractor.
- 11.2. The tenderer shall guarantee among other things, the following:
- 11.2.1. Quality, strength and performance of the material used as per manufacturer's standards.
- 11.2.2. Safe mechanical and electrical stress on all part under all specified conditions of operation.
- 11.2.3. Satisfactory operation during the maintenance period.

12. POWER SUPPLY

12.1. It is clarified that electricity will be provided from the existing connection near building and necessary arrangement for tapping and termination of supply will be done by the contractor. The charges for electricity may be recovered from the running account bill of the contractor as per the bill raised by IIT Delhi authorities.

13. DATA MANUAL AND DRAWING TO BE FURNISHED BY THE TENDERER

- 13.1. With tender: The tenderer shall furnish along with the tender, detailed technical literature, pamphlets and performance date for appraisal and evaluation of the offer.
- 13.2. The successful tender should furnish well in advance three copies of detailed instruction and manuals of manufacturer's for all items of equipments regarding installation, adjustment operation and maintenance including preventative maintenance and troubleshooting together with all the relevant date sheets, spare parts catalogue etc. all in triplicate.

14. EXTENT OF WORK

14.1. The work shall comprise of entire labour including supervision and all material necessary to make a complete installation and such tests and adjustment and commissioning as may be required by the department. The term complete installation shall not only mean major items of the plant and equipments covered by the specification but all incidental sundry components necessary for complete execution and satisfactory performance of installation with all layout charts whether or not those have been mentioned in details in the tender documents in connection with this contract as this is a turnkey job.

Page **33** of **64**



- 14.1.1. Minor building works necessary for installation of equipments, foundation making of opening in walls or in floors and restoring them to their original condition / finish and necessary grouting etc. as required.
- 14.1.2. All supports for cable and MS Channel for erection as are necessary.

15. INSPECTION AND TESTING

- 15.1. The material and equipments shall be offered for initial inspection at manufacturer's works. The contactor will intimate the date of testing of equipments at the manufacturer's work before dispatch. The successful tenderer shall give advance notice of minimum two weeks regarding the dates proposed for such test to the department representative to facilitate his presence during testing. The Engineer- in-charge may witness such testing. The cost of the Engineer visit to the factory will be borne by the Department. Equipments will be inspected at the manufacturer premises before dispatch to the site. Nothing extra shall be paid for initial inspection/testing at Manufacture Works.
- 15.2. Copies of all documents of routine and type test certificates of the equipment carried out at the manufactures premises shall be furnished to the Engineer-in- charge and consignee.

16. VALIDITY

16.1. Tenders shall be valid for acceptance for a period 90 days of days from the date of opening of price bid.

17. COMPLIANCE WITH REGULATIONS AND INDIAN STANDARDS

- **17.1.** All works shall be carried out in accordance with relevant regulation both statutory and those specified by the Indian Standards related to the works covered by this specification in particular, the equipment and installation will comply with the following:
- 17.1.1. Factories Act
- 17.1.2. Indian Electricity Rules
- **17.1.3.** B.I.S. & other standards as applicable
- **17.1.4.** Workmen's compensation Act
- 17.1.5. Statutory norms prescribed by local bodies like fire department, CEA, Power Supply Co. etc.
- 17.1.6. After completion of the installation the same may be offered for inspection by the representatives of the Inspection Deptt of Delhi Govt. The contractor will extend all help including test facilities to the representatives of Inspector. The observation of Inspector will be attended by the contractor.
- 17.1.7. Nothing in this specification shall be construed to relieve the successful tender of his responsibility for the design, manufacture and installation of the equipment with all accessories in accordance with currently applicable statutory regulations and safety codes.
- 17.1.8. Successful tenderer shall arrange for compliance with statutory provisions of safety regulations and departmental requirements of safety codes in respect of labour employed on the work by the tenderer. Failure to provide such safety requirements would make the tenderer liable for

Page 34 of 64



penalty of Rs.200/- for each default. In addition, the department will be at liberty to make arrangement for safety requirements at the cost of tenderer and recover the cost thereof from him.

18. INDEMNITY

18.1. The successful tenderer shall at all times indemnify the department, consequent on this works contract. The successful tenderer shall be liable, in accordance with the Indian Law and Regulations for any accident occurring due to any cause and the contractor shall be responsible for any accident or damage incurred or claims arising there from during the period of erection, construction and putting into operation the equipments and ancillary equipment under the supervision of the successful tenderer in so far as the latter is responsible. The successful tenderer shall also provide all insurance including third party insurance as may be necessary to cover the risk. No extra payment would be made to the successful tenderer on account of the above.

19. ERECTION TOOLS

19.1. No tools and tackles either for unloading or for shifting the equipments for erection purposes would be made available by the department .The successful tender shall make his arrangement for all these facilities

20. COOPERATION WITH OTHER AGENCIES AND OCCUPANTS OF THE BUILDING

20.1. The successful tenderer shall co-ordinate with other working contractors, if any and other occupants of different offices / Labs, etc., and exchange freely all technical information so as to make the execution of this work / contract smooth. No remuneration should be claimed from the department for such technical cooperation. If any unreasonable hindrance is caused to other agencies and any completed portion of the work has to be dismantled and re-done for want or cooperation and coordination by the tenderer during the course of work, such expenditure incurred will be recovered from the successful tenderer if the restoration work to the original condition or specification of the dismantled portion of work was not under taken by the tenderer himself.

21. MOBILIZATION ADVANCE

21.1. No mobilization advance shall be paid for this work

22. INSURANCE AND STORAGE

22.1. All consignments are to be duly insured upto the destination from warehouse at the cost of the contractor. The insurance covers shall be valid till the equipment is handed over duly installed, tested and commissioned.

23. TRAINING

23.1. The scope of work includes the on job technical training of two persons of department at site. Nothing extra shall be payable on this account.

24. MAINTENANCE

Page **35** of **64**



- **24.1.** Sufficient trained and experienced staff shall be made available to meet any exigency of work during the guarantee period of one year from the handing over of the installation.
- **24.2.** The maintenance, routine as well as preventative for the first year from the date of taking over the installation as per manufactures recommendation shall be carried out free of cost.
- 24.3. A separate supplementary agreement shall be made with the successful tenderer for Sub Head II of Schedule of Work i.e. Comprehensive Maintenance for 5 years after guarantee period of 1 year. The payment for comprehensive maintenance shall be made quarterly after the end of each quarter.

25. INTERPRETING SPECIFICATION

- **25.1.** In interpreting the specification, the following order of decreasing importance shall be followed in case of contradictions:
- 25.1.1. Schedule of quantities
- 25.1.2. Technical Specification
- **25.1.3.** Drawing (if any)
- **25.1.4.** General Specification for Electrical Works of CPWD (relevant Parts)
- **25.1.5.** Relevant BIS or other international code in case BIS code is not available.

26. POLICY OF THE INSTITUTE

26.1. Institute has a policy against **sexual harassment** and is committed to providing an environment free from **sexual harassment of women** at the workplace. Contractor shall have to abide by the policy of the Institute with due diligence. Any violation on the part of the contractor shall be dealt with the extant rules of the Institute.

Page 36 of 64



ADDITIONAL SPECIFICATIONS FOR PASSENGER LIFTS

Location:- MSB Building

	AUDII MISD BUIIUIIIY							
1	Type of Lift	:	PASSENGER					
2	Number of lifts required [Location wise]	:	02 (Two)					
3	Load: Number of persons	:	544 kg : 08 Passenger per each lift					
4	Rated speed	:	1.5 MPS					
5	Travel in meters		25 m (approx.)					
6	Number of floors served	:	G + 6 Floors [G, 1, 2, 3, 4, 5, 6]					
7	[a] Inside size of lift well	:	Available well size is about 1550(D) mm x 2040(W) mm for Right Elevator. Available well size is about 1650(D) mm x 1980(W) mm for Left Elevator.					
	[b] Pit depth	:	1600 mm					
8	Clear inside size of lift car	:	About 1100 mm x 1300 mm or as per shaft availability.					
9	Dimension of lift machine room	:	Machine room as per construction					
10	Position of counter weight	:	At the back / side of the car					
11	Position of machine room	:	At the top of the lift shaft					
12 [a]	Type of control	:	Microprocessor based AC variable voltage variable frequency & Gearless					
[b]	Type of operation	:	Duplex selective-collective operation with / without attendant					
[c]	Potential free contacts	: Potential free contacts for each floor position and up and down movement of the lift shall be provided in the controller which can be used for the building automation system at later date for monitoring only.						
13	Car entrance door		Stainless Steel [Linen] Finish Doors.					
[a]	Number	:	One					
[b]	Size		Not less than 900 mm x 2000 mm [Height]					
[c]	Type of doors	:	Horizontal sliding – centre opening					
[d]	Car open in front only or open	:	In front only					
14	Construction design and finish of car body work	:	Stainless steel [Linen finish]					
15	Type of signal system							
[a]								
[b]	Travel direction indicator in the car and at all landings [to be provided above the car / landing doors]							
[c]	Gongs and visual indication on all landings for pre arrival of the car for two or more cars							

Page **37** of **64**



on overload (e) Battery operated alarm bell and emergency light (f) Car operating panel with fade proof luminous buttons in car and with intercom (g) Luminous hall buttons at all landings (h) Fireman's switch at ground floor (i) Hall position indicators and buttons shall be Segment LED Indicators, Tactile button along with additional Braille inscriptions. (ii) Fire Emergency Return: Upon activation of a key switch or a building's fire alarm, all calls are canceled, all cars immediately return to a specified evacuation floor and the doors open to facilitate the safe evacuation of passengers. Emergency Car Lighting: Car lighting which turns on immediately when power fails, providing a minimum level of lighting within the car. (k) Emergency Landing Device (Automatic rescue Device) with audio announcer: Upon power failure, a car equipped with this function automatically moves and stops at the nearest floor using a rechargeable battery, and the doors open to facilitate the safe evacuation of passengers with audio announcer. Dry type Battery (Maintenance Free) should be used for power backup.	[d]	Overload warning Audio & Visual indicator, inside the car [lift should not start					
 [f] Car operating panel with fade proof luminous buttons in car and with intercom [g] Luminous hall buttons at all landings [h] Fireman's switch at ground floor [i] Hall position indicators and buttons shall be Segment LED Indicators, Tactile button along with additional Braille inscriptions. [j] Fire Emergency Return: Upon activation of a key switch or a building's fire alarm, all calls are canceled, all cars immediately return to a specified evacuation floor and the doors open to facilitate the safe evacuation of passengers. [k] Emergency Car Lighting: Car lighting which turns on immediately when power fails, providing a minimum level of lighting within the car. [k] Emergency Landing Device (Automatic rescue Device) with audio announcer: Upon power failure, a car equipped with this function automatically moves and stops at the nearest floor using a rechargeable battery, and the doors open to facilitate the safe evacuation of passengers with audio announcer. Dry type Battery (Maintenance Free) should be used for power backup. [i] Automatic speed control: Door load on each floor, which can depend on the type of hall doors, is monitored to adjust the door speed, thereby making the door speed consistent throughout all floors. [m] Door load detector: When excessive door load has been detected while opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to conserve energy. [r] False Call Canceling— Automatic, If then umber of registered car calls does not Cor							
 [g] Luminous hall buttons at all landings [h] Fireman's switch at ground floor [i] Hall position indicators and buttons shall be Segment LED Indicators, Tactile button along with additional Braille inscriptions. [j] Fire Emergency Return: Upon activation of a key switch or a building's fire alarm, all calls are canceled, all cars immediately return to a specified evacuation floor and the doors open to facilitate the safe evacuation of passengers. Emergency Car Lighting: Car lighting which turns on immediately when power fails, providing a minimum level of lighting within the car. [k] Emergency Landing Device (Automatic rescue Device) with audio announcer: Upon power failure, a car equipped with this function automatically moves and stops at the nearest floor using a rechargeable battery, and the doors open to facilitate the safe evacuation of passengers with audio announcer. Dry type Battery (Maintenance Free) should be used for power backup. [ii] Automatic speed control: Door load on each floor, which can depend on the type of hall doors, is monitored to adjust the door speed, thereby making the door speed consistent throughout all floors. [m] Door load detector: When excessive door load has been detected while opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period, the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to conserve energy. [r] False Call Canceling — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [s] False Call Canceling — Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pres							
 [h] Fireman's switch at ground floor [i] Hall position indicators and buttons shall be Segment LED Indicators, Tactile button along with additional Braille inscriptions. [j] Fire Emergency Return: Upon activation of a key switch or a building's fire alarm, all calls are canceled, all cars immediately return to a specified evacuation floor and the doors open to facilitate the safe evacuation of passengers. Emergency Car Lighting: Car lighting which turns on immediately when power fails, providing a minimum level of lighting within the car. [k] Emergency Landing Device (Automatic rescue Device) with audio announcer: Upon power failure, a car equipped with this function automatically moves and stops at the nearest floor using a rechargeable battery, and the doors open to facilitate the safe evacuation of passengers with audio announcer. Dry type Battery (Maintenance Free) should be used for power backup. [ii] Automatic speed control: Door load on each floor, which can depend on the type of hall doors, is monitored to adjust the door speed, thereby making the door speed consistent throughout all floors. [m] Door load detector: When excessive door load has been detected while opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong							
 [I] Hall position indicators and buttons shall be Segment LED Indicators, Tactile button along with additional Braille inscriptions. [I] Fire Emergency Return: Upon activation of a key switch or a building's fire alarm, all calls are canceled, all cars immediately return to a specified evacuation floor and the doors open to facilitate the safe evacuation of passengers. Emergency Car Lighting: Car lighting which turns on immediately when power fails, providing a minimum level of lighting within the car. [K] Emergency Landing Device (Automatic rescue Device) with audio announcer: Upon power failure, a car equipped with this function automatically moves and stops at the nearest floor using a rechargeable battery, and the doors open to facilitate the safe evacuation of passengers with audio announcer. Dry type Battery (Maintenance Free) should be used for power backup. [I] Automatic speed control: Door load on each floor, which can depend on the type of hall doors, is monitored to adjust the door speed, thereby making the door speed consistent throughout all floors. [m] Door load detector: When excessive door load has been detected while opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly							
 button along with additional Braille inscriptions. [j] Fire Emergency Return: Upon activation of a key switch or a building's fire alarm, all calls are canceled, all cars immediately return to a specified evacuation floor and the doors open to facilitate the safe evacuation of passengers. Emergency Car Lighting: Car lighting which turns on immediately when power fails, providing a minimum level of lighting within the car. [k] Emergency Landing Device (Automatic rescue Device) with audio announcer: Upon power failure, a car equipped with this function automatically moves and stops at the nearest floor using a rechargeable battery, and the doors open to facilitate the safe evacuation of passengers with audio announcer. Dry type Battery (Maintenance Free) should be used for power backup. [l] Automatic speed control: Door load on each floor, which can depend on the type of hall doors, is monitored to adjust the door speed, thereby making the door speed consistent throughout all floors. [m] Door load detector: When excessive door load has been detected while opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to conserve energy. [s] False Call Canceling— Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to conserve energy. [s] False Call Canceling— Car Button Type Automatic							
alarm, all calls are canceled, all cars immediately return to a specified evacuation floor and the doors open to facilitate the safe evacuation of passengers. Emergency Car Lighting: Car lighting which turns on immediately when power fails, providing a minimum level of lighting within the car. [k] Emergency Landing Device (Automatic rescue Device) with audio announcer: Upon power failure, a car equipped with this function automatically moves and stops at the nearest floor using a rechargeable battery, and the doors open to facilitate the safe evacuation of passengers with audio announcer. Dry type Battery (Maintenance Free) should be used for power backup. [I] Automatic speed control: Door load on each floor, which can depend on the type of hall doors, is monitored to adjust the door speed, thereby making the door speed consistent throughout all floors. [m] Door load detector: When excessive door load has been detected while opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the presst period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [s] False Call Canceling — Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling — Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors		button along with additional Braille inscriptions.					
 power fails, providing a minimum level of lighting within the car. [K] Emergency Landing Device (Automatic rescue Device) with audio announcer: Upon power failure, a car equipped with this function automatically moves and stops at the nearest floor using a rechargeable battery, and the doors open to facilitate the safe evacuation of passengers with audio announcer. Dry type Battery (Maintenance Free) should be used for power backup. [II] Automatic speed control: Door load on each floor, which can depend on the type of hall doors, is monitored to adjust the door speed, thereby making the door speed consistent throughout all floors. [m] Door load detector: When excessive door load has been detected while opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [s] False Call Canceling — Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling — Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service - If a car h	[[J]	alarm, all calls are canceled, all cars immediately return to a specified evacuation floor and the doors open to facilitate the safe evacuation of passengers.					
 announcer: Upon power failure, a car equipped with this function automatically moves and stops at the nearest floor using a rechargeable battery, and the doors open to facilitate the safe evacuation of passengers with audio announcer. Dry type Battery (Maintenance Free) should be used for power backup. [II] Automatic speed control: Door load on each floor, which can depend on the type of hall doors, is monitored to adjust the door speed, thereby making the door speed consistent throughout all floors. [m] Door load detector: When excessive door load has been detected while opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling — Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling — Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service - If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, th		power fails, providing a minimum level of lighting within the car.					
type of hall doors, is monitored to adjust the door speed, thereby making the door speed consistent throughout all floors. [m] Door load detector: When excessive door load has been detected while opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open.	[k]	Emergency Landing Device (Automatic rescue Device) with audio announcer: Upon power failure, a car equipped with this function automatically moves and stops at the nearest floor using a rechargeable battery, and the doors open to facilitate the safe evacuation of passengers with audio announcer. Dry type Battery (Maintenance Free) should be used for power backup.					
 door speed consistent throughout all floors. [m] Door load detector: When excessive door load has been detected while opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open. 	[1]						
 [m] Door load detector: When excessive door load has been detected while opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open. 							
opening or closing, the doors Door Load Detector immediately reverse. [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open.							
 [n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling — Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling — Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open. 	[m]						
 [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open. 	[n]						
the door height of the doors to detect passengers or objects as the doors close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open.							
 close. [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open. 	[0]	·					
 [p] Car Fan Shut Off — Automatic, If there are no calls for a specified period, the car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open. 							
 car ventilation fan will automatically turn off to conserve energy. [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open. 	[q]						
 [q] Car Light Shut Off — Automatic, If there are no calls for a specified period, the car lighting will automatically turn off to Conserve energy. [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open. 							
 [r] False Call Canceling— Automatic, If the number of registered car calls does not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open. 	[q]	Car Light Shut Off — Automatic, If there are no calls for a specified period, the					
not Correspond to the car load, all calls are canceled to avoid unnecessary stops. [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open.	[r]						
 [s] False Call Canceling— Car Button Type Automatic, If a wrong car button is pressed, it can be canceled by quickly pressing the same button again twice. [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open. 	L. J	not Correspond to the car load, all calls are canceled to avoid unnecessary					
pressed, it can be canceled by quickly pressing the same button again twice. Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open.							
 [t] Overload Holding Stop A buzzer sounds to alert the passengers that the car is overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open. 	[s]	· · · · · · · · · · · · · · · · · · ·					
overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open.	F47						
enough passengers exit the car. [u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open.	[t]	, ,					
[u] Safe Landing Service- If a car has stopped between floors due to some equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open.							
equipment malfunction, the controller checks the cause, and if it is considered safe to move the car, the car will move to the nearest floor at a low speed and the doors will open.	[11]						
safe to move the car, the car will move to the nearest floor at a low speed and the doors will open.	լսյ						
the doors will open.		• •					
·		•					
	[v]	LCD / LED Position Indicator 5-7-inch LCD / LED for car operating panels					

Page **38** of **64**



.... 10 tes.

	shows the date and time, car position, travel direction and elevator status messages.					
[w]			Display 5 to 7 inch LCD / LED for elevator position, travel direction and elevator status			
[x]	Provision of CCTV and Intercor	m ii	ncluding wiring.			
[y]	Provision of Floor announceme	ent	with all time music.			
[z]	Provision of Single Phase/ phase/ correction of phase reversal.	ase	e failure sensing for ARD along with auto			
16	Landing entrance					
[a]	Location of landing entrance in different floors	:	All doors on the same side			
[b]	Number	:	G, 1, 2, 3, 4, 5, 6.			
[c]	Size	•	Not less than 900 mm x 2000 mm [h]			
[d]	Type of doors	:	Horizontal sliding centre opening			
[e]	Lift in use / lift out of order sign	:	A suitable box above the lift landing with LED illuminated [in English / Hindi] sign of "LIFT OUT OF ORDER" coming up simultaneously at all floors			
17	Electric supply	:	[a] Power: 415 V, a.c., 3 phase, 50 Hz, 4 wire system			
40			[b] Lighting: 230 V, 50 Hz, a.c.			
18	Is neutral wire available for control circuits	:	Yes			
19	Proposed date for commencement on site	:	As per contract			
20	Proposed date for completion	:	As per contract			
21	Environmental condition at site of installation	:	Summer condition			
			Winter condition			
			Monsoon condition			
			Height above sea level			
22	Traction System	:	Rope-in- belt driven technology			
23	Fire Rating	:	2 Hour fire rating landing doors (certification required)			
24	Car Flooring	<u> </u> :	Natural granite flooring			
25	Door sensor	:	Light curtain protection on door			
26	Car and landing operation panel	:	Tactile push button along with additional Braille inscriptions.			
27	Ventilation	:	Noiseless type fans (blowers) of appropriate throw of CFM inside the car			
28	Mirror	<u> </u>	Full length mirror on rear side			
29	Confirming to Quality Standard IS/ISO-9001:2015		IS/ISO-9001:2015			



30	IoT cloud-based device	device OEM itself having the Intellectual Property Rights					
Loca	Location:- Vishwakarma Bhawan						
1	Type of Lift	:	PASSENGER				
2	Number of lifts required	:	01 (One)				
	[Location wise]		` '				
3	Load: Number of persons	:	544 kg : 08 Passenger per each lift				
4	Rated speed	:	1.5 MPS				
5	Travel in meters	:	24 m (approx.)				
6	Number of floors served	:	B + G + 6 Floors [B, G, 1, 2, 3, 4, 5, 6]				
7	[a] Inside size of lift well	:	Available well size is about 1540 (W) mm				
			x 1400(D) mm				
	[b] Pit depth	:	1500 mm				
8	Clear inside size of lift car	:	About 1100 mm x 1300 mm or As per Shaft Availability.				
9	Dimension of lift machine room	:	Machine room as per construction				
10	Position of counter weight	:	At the back / side of the car				
11	Position of machine room	:	At the top of the lift shaft				
12	Type of control	:	Microprocessor based AC variable voltage				
[a]			variable frequency & Gearless				
[b]	Type of operation	:	Simplex selective-collective operation with / without attendant				
[c]	Potential free contacts	: Potential free contacts for each flo position and up and down movement of the lift shall be provided in the controller which can be used for the building automatic system at later date for monitoring only.					
13	Car entrance door		Stainless Steel [Linen] Finish Doors.				
[a]	Number	:	One				
[b]	Size	:	Not less than 800 mm x 2000 mm [Height]				
[c]	Type of doors	:	Horizontal sliding – centre opening / Telescopic				
[d]	Car open in front only or open	:	In front only				
14	Construction design and finish	:	Stainless steel [Linen finish]				
_	of car body work						
15	Type of signal system	<u> </u>					
[a]	[a] Digital floor position indicator in the car and at all landings [to be provided above the car / landing doors]						
[b]	the car / landing doors]		ar and at all landings [to be provided above				
[c]	Gongs and visual indication on more cars	all	landings for pre arrival of the car for two or				
[d]		ıal	indicator, inside the car [lift should not start				

Page **40** of **64**



-4 10 III--

[e]	Battery operated alarm bell and emergency light
[f]	Car operating panel with fade proof luminous buttons in car and with intercom
[g]	Luminous hall buttons at all landings
[h]	Fireman's switch at ground floor
[i]	Hall position indicators and buttons shall be Segment LED Indicators, Tactile
	button along with additional Braille inscriptions.
[j]	Fire Emergency Return: Upon activation of a key switch or a building's fire
	alarm, all calls are canceled, all cars immediately return to a specified
	evacuation floor and the doors open to facilitate the safe evacuation of
	passengers.
	Emergency Car Lighting: Car lighting which turns on immediately when
[]-1	power fails, providing a minimum level of lighting within the car.
[k]	Emergency Landing Device (Automatic rescue Device) with audio announcer: Upon power failure, a car equipped with this function
	automatically moves and stops at the nearest floor using a rechargeable
	battery, and the doors open to facilitate the safe evacuation of passengers
	with audio announcer. Dry type Battery (Maintenance Free) should be used
	for power backup.
[1]	Automatic speed control: Door load on each floor, which can depend on the
	type of hall doors, is monitored to adjust the door speed, thereby making the
	door speed consistent throughout all floors.
[m]	Door load detector: When excessive door load has been detected while
[n]	opening or closing, the doors Door Load Detector immediately reverse. Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly
ניין	close when they have remained open for longer than the preset period.
[0]	Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of
[O]	the door height of the doors to detect passengers or objects as the doors
	close.
[p]	Car Fan Shut Off — Automatic, If there are no calls for a specified period, the
" -	car ventilation fan will automatically turn off to conserve energy.
[q]	Car Light Shut Off — Automatic, If there are no calls for a specified period, the
	car lighting will automatically turn off to Conserve energy.
[r]	False Call Canceling— Automatic, If the number of registered car calls does
	not Correspond to the car load, all calls are canceled to avoid unnecessary
	stops.
[s]	False Call Canceling— Car Button Type Automatic, If a wrong car button is
F47	pressed, it can be canceled by quickly pressing the same button again twice.
[t]	Overload Holding Stop A buzzer sounds to alert the passengers that the car is
	overloaded. The doors remain open and the car will not leave that floor until
[u]	enough passengers exit the car. Safe Landing Service- If a car has stopped between floors due to some
լսյ	equipment malfunction, the controller checks the cause, and if it is considered
	safe to move the car, the car will move to the nearest floor at a low speed and
	the doors will open.
[v]	LCD / LED Position Indicator 5-7-inch LCD / LED for car operating panels
	shows the date and time, car position, travel direction and elevator status
	messages.

Page **41** of **64**



∞4 to 10.10 to 10.10

[w]	Hall LCD / LED Position Indicator Display 5 to 7inch LCD / LED for elevator				
	messages.	car	position, travel direction and elevator status		
[x]	Provision of CCTV and Intercor		ocluding wiring		
	Provision of Floor announcement		•		
[y] [z]			e failure sensing for ARD along with auto		
[2]	correction of phase reversal.	ase	e failure sensing for ARD along with auto		
16	Landing entrance				
[a]	Location of landing entrance in different floors	:	All doors on the same side		
[b]	Number	:	B, G, 1, 2, 3, 4, 5, 6.		
[c]	Size	•••	Not less than 800 mm x 2000 mm [h]		
[d]	Type of doors	••	Horizontal sliding centre opening/ Telescopic		
[e]	Lift in use / lift out of order sign	:	A suitable box above the lift landing with LED illuminated [in English / Hindi] sign of "LIFT OUT OF ORDER" coming up simultaneously at all floors		
17	Electric supply	:	[a] Power: 415 V, a.c., 3 phase, 50 Hz, 4 wire system		
			[b] Lighting: 230 V, 50 Hz, a.c.		
18	Is neutral wire available for control circuits	:	Yes		
19	Proposed date for commencement on site	:	As per contract		
20	Proposed date for completion	:	As per contract		
21	Environmental condition at site of installation	:	Summer condition		
			Winter condition		
			Monsoon condition		
			Height above sea level		
22	Traction System	:	Rope-in- belt driven technology		
23	Fire Rating	:	2 Hours fire rating landing doors (certification required)		
24	Car Flooring	•••	Natural granite flooring		
25	Door sensor	:	Light curtain protection on door		
26	Car and landing operation panel	:	Tactile push button along with additional Braille inscriptions.		
27	Ventilation	•••	Noiseless type fans (blowers) of		
			appropriate throw of CFM inside the car		
28	Mirror	:	Full length mirror on rear side		
29	Confirming to Quality Standard IS/ISO-9001:2015		IS/ISO-9001:2015		



30	IoT cloud-based device	OEM	itself	having	the	Intellectual
		Prope	rty Rig	hts		

Location:- Taxila Apartment

	ocation Taxila Apartinent						
1	Type of Lift	:	PASSENGER				
2	Number of lifts required	:	01 (One)				
	[Location wise]						
3	Load: Number of persons	:	544 kg : 08 Passenger per each lift				
4	Rated speed	:	1.5 MPS				
5	Travel in meters	:	16 m (approx.)				
6	Number of floors served	:	G + 5 Floors [G, 1, 2, 3, 4, 5]				
7	[a] Inside size of lift well	:	Available well size is about 1860(W) mm x				
			1850(D) mm				
	[b] Pit depth	:	1600 mm				
8	Clear inside size of lift car		About 1100 mm x 1300 mm or As per Shaft				
			Availability.				
9	Dimension of lift machine	:	Machine room as per construction				
	room						
10	Position of counter weight	:	At the back / side of the car				
11	Position of machine room	:	At the top of the lift shaft				
12	Type of control		Microprocessor based AC variable voltage				
[a]			variable frequency & Gearless				
[b]	Type of operation	:	Simplex selective-collective operation with				
			/ without attendant				
[c]	Potential free contacts	:	Potential free contacts for each floor				
			position and up and down movement of the				
			lift shall be provided in the controller which				
			can be used for the building automation				
			system at later date for monitoring only.				
13	Car entrance door		Stainless Steel [Linen] Finish Doors.				
[a]	Number	:	One				
[b]	Size	:	Not less than 800 mm x 2000 mm [Height]				
[c]	Type of doors	:	Horizontal sliding – Centre opening				
[d]	Car open in front only or open	:	In front only				
14	Construction design and finish	:	Stainless steel [Linen finish]				
	of car body work						
15	Type of signal system						
[a]		in t	he car and at all landings [to be provided				
	above the car / landing doors]						
[b]	Travel direction indicator in the	ca	ar and at all landings [to be provided above				
• •	the car / landing doors]						
[c]	Gongs and visual indication on all landings for pre arrival of the car for two or						
	more cars						



on overload] [e] Battery operated alarm bell and emergency light	
[f] Car operating panel with fade proof luminous buttons in car and with int	tercom
[g] Luminous hall buttons at all landings	
[h] Fireman's switch at ground floor	
[i] Hall position indicators and buttons shall be Segment LED Indicators, button along with additional Braille inscriptions.	Tactile
[j] Fire Emergency Return: Upon activation of a key switch or a building	's fire
alarm, all calls are canceled, all cars immediately return to a spe	
evacuation floor and the doors open to facilitate the safe evacuati	on of
passengers.	
Emergency Car Lighting: Car lighting which turns on immediately when	
power fails, providing a minimum level of lighting within the car.	
[k] Emergency Landing Device (Automatic rescue Device) with	
announcer: Upon power failure, a car equipped with this fur	
automatically moves and stops at the nearest floor using a recharg battery, and the doors open to facilitate the safe evacuation of passe	
with audio announcer. Dry type Battery (Maintenance Free) should be	
for power backup.	uscu
[I] Automatic speed control: Door load on each floor, which can depend	on the
type of hall doors, is monitored to adjust the door speed, thereby making	
door speed consistent throughout all floors.	
[m] Door load detector: When excessive door load has been detected	
opening or closing, the doors Door Load Detector immediately reverse.	
[n] Door Nudging Feature — With Buzzer: A buzzer sounds and the doors s	
close when they have remained open for longer than the preset period. [o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2	
[o] Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2 the door height of the doors to detect passengers or objects as the o	
close.	20013
[p] Car Fan Shut Off — Automatic, If there are no calls for a specified period	od, the
car ventilation fan will automatically turn off to conserve energy.	,
[q] Car Light Shut Off — Automatic, If there are no calls for a specified period	od, the
car lighting will automatically turn off to Conserve energy.	
[r] False Call Canceling— Automatic, If the number of registered car calls	
not Correspond to the car load, all calls are canceled to avoid unnec	essary
stops.	
[s] False Call Canceling— Car Button Type Automatic, If a wrong car but the control of the contr	
pressed, it can be canceled by quickly pressing the same button again	
[t] Overload Holding Stop A buzzer sounds to alert the passengers that the	
overloaded. The doors remain open and the car will not leave that floo	or until
enough passengers exit the car.[u] Safe Landing Service- If a car has stopped between floors due to	somo
equipment malfunction, the controller checks the cause, and if it is cons	
safe to move the car, the car will move to the nearest floor at a low spec	
the doors will open.	23 3113
[v] LCD / LED Position Indicator 5-7-inch LCD / LED for car operating	panels

Page **44** of **64**



	1 4 1 6 1 6					
	shows the date and time, car position, travel direction and elevator status					
	messages.					
[w]	Hall LCD / LED Position Indicator Display 5 to 7 inch LCD / LED for elevator					
	halls shows the date and time, car position, travel direction and elevator status					
	messages.					
[x]	Provision of CCTV and Intercor					
[y]	Provision of Floor announcement					
[z]		ase	e failure sensing for ARD along with auto			
	correction of phase reversal.					
16	Landing entrance					
[a]	Location of landing entrance	:	All doors on the same side			
	in different floors					
[b]	Number	:	G, 1, 2, 3, 4, 5			
	0.		N. d. ale ale			
[c]	Size	:	Not less than 800 mm x 2000 mm [h]			
[d]	Type of doors	:	Horizontal sliding centre opening			
[e]	Lift in use / lift out of order sign	:	A suitable box above the lift landing with			
			LED illuminated [in English / Hindi] sign of			
			"LIFT OUT OF ORDER" coming up			
			simultaneously at all floors			
17	Electric supply	:	[a] Power: 415 V, a.c., 3 phase, 50 Hz, 4			
			wire system			
			[b] Lighting: 230 V, 50 Hz, a.c.			
18	Is neutral wire available for	:	Yes			
	control circuits					
19	Proposed date for	:	As per contract			
	commencement on site					
20	Proposed date for completion	:	As per contract			
21	Environmental condition at	:	Summer condition			
	site of installation					
			Winter condition			
			Monsoon condition			
			Height above sea level			
22	Traction System	:	Rope-in- belt driven technology			
23	Fire Rating	:	2 Hours fire rating landing doors			
			(certification required)			
24	Car Flooring	:	Natural granite flooring			
25	Door sensor	:	Light curtain protection on door			
26	Car and landing operation	:	Tactile push button along with additional			
	panel		Braille inscriptions.			
27	Ventilation	:	Noiseless type fans (blowers) of			
			appropriate throw of CFM inside the car			
28	Mirror	:	Full length mirror on rear side			
29	Confirming to Quality		IS/ISO-9001:2015			
	Standard					
	IS/ISO-9001:2015					



30	IoT cloud-based device	OEM	itself	having	the	Intellectual
		Prope	rty Rig	hts		

Location:- Synergy Building

1	Type of Lift	:	PASSENGER			
2	Number of lifts required	:	01 (One)			
	[Location wise]		,			
3	Load: Number of persons	:	544 kg : 08 Passenger per each lift			
4	Rated speed	:	1.5 MPS			
5	Travel in meters	:	14 m (approx.)			
6	Number of floors served	:	G + 3 Floors [G, 2, 3, 4]			
7	[a] Inside size of lift well	:	Available well size is about 1680(D) mm x			
			2250(W) mm			
	[b] Pit depth	:	1600 mm			
8	Clear inside size of lift car	:	About 1100 mm x 1300 mm or As per Shaft			
			Availability.			
9	Dimension of lift machine	:	Machine room as per construction			
	room					
10	Position of counter weight	:	At the back side of the car			
11	Position of machine room	:	At the top of the lift shaft			
12	Type of control	:	Microprocessor based AC variable voltage			
[a]			variable frequency & Gearless			
[b]	Type of operation	:	Simplex selective-collective operation with			
	5		/ without attendant			
[c]	Potential free contacts	:	Potential free contacts for each floor			
			position and up and down movement of the			
			lift shall be provided in the controller which			
			can be used for the building automation system at later date for monitoring only.			
13	Car entrance door		Stainless Steel [Linen] Finish Doors.			
[a]	Number		One			
[b]	Size	-	Not less than 900 mm x 2000 mm [Height]			
[c]	Type of doors	:	Horizontal sliding – centre opening			
[d]	Car open in front only or open	:	In front only			
14	Construction design and finish	:	Stainless steel [Linen finish]			
	of car body work	-	2 2 [
15	Type of signal system					
[a]		in t	he car and at all landings [to be provided			
• •	above the car / landing doors]		3.1			
[b]	Travel direction indicator in the	e Ca	ar and at all landings [to be provided above			
[]	the car / landing doors]					
[c]	Gongs and visual indication on all landings for pre arrival of the car for two or					
	· ·					
	more cars					



[d]	Overload warning Audio & Visual indicator, inside the car [lift should not start
	on overload]
[e]	Battery operated alarm bell and emergency light
[f]	Car operating panel with fade proof luminous buttons in car and with intercom
[g]	Luminous hall buttons at all landings
[h]	Fireman's switch at ground floor
[i]	Hall position indicators and buttons shall be Segment LED Indicators, Tactile button along with additional Braille inscriptions.
[j]	Fire Emergency Return: Upon activation of a key switch or a building's fire
.,,	alarm, all calls are canceled, all cars immediately return to a specified
	evacuation floor and the doors open to facilitate the safe evacuation of
	passengers.
	Emergency Car Lighting: Car lighting which turns on immediately when
	power fails, providing a minimum level of lighting within the car.
[k]	Emergency Landing Device (Automatic rescue Device) with audio
	announcer: Upon power failure, a car equipped with this function
	automatically moves and stops at the nearest floor using a rechargeable battery, and the doors open to facilitate the safe evacuation of passengers
	with audio announcer. Dry type Battery (Maintenance Free) should be used
	for power backup.
[1]	Automatic speed control: Door load on each floor, which can depend on the
	type of hall doors, is monitored to adjust the door speed, thereby making the
	door speed consistent throughout all floors.
[m]	Door load detector: When excessive door load has been detected while
	opening or closing, the doors Door Load Detector immediately reverse.
[n]	Door Nudging Feature — With Buzzer: A buzzer sounds and the doors slowly
[o]	close when they have remained open for longer than the preset period. Multi-beam Door Sensor: Multiple infrared-light beams cover at least 2/3 of
[0]	the door height of the doors to detect passengers or objects as the doors
	close.
[p]	Car Fan Shut Off — Automatic, If there are no calls for a specified period, the
	car ventilation fan will automatically turn off to conserve energy.
[q]	Car Light Shut Off — Automatic, If there are no calls for a specified period, the
	car lighting will automatically turn off to Conserve energy.
[r]	False Call Canceling— Automatic, If the number of registered car calls does
	not Correspond to the car load, all calls are canceled to avoid unnecessary
	stops.
[s]	False Call Canceling— Car Button Type Automatic, If a wrong car button is
F43	pressed, it can be canceled by quickly pressing the same button again twice.
[t]	Overload Holding Stop A buzzer sounds to alert the passengers that the car is
	overloaded. The doors remain open and the car will not leave that floor until enough passengers exit the car.
[u]	Safe Landing Service- If a car has stopped between floors due to some
[[4]	equipment malfunction, the controller checks the cause, and if it is considered
	safe to move the car, the car will move to the nearest floor at a low speed and
	the doors will open.
[v]	LCD / LED Position Indicator 5 to 7 inch LCD / LED for car operating panels

Page **47** of **64**



	shows the date and time, car position, travel direction and elevator status								
	messages.								
[w]	Hall LCD / LED Position Indica	tor	Display 5 to 7 inch LCD / LED for elevator						
	halls shows the date and time,	car	position, travel direction and elevator status						
	messages.								
[x]	Provision of CCTV and Interco	m i	ncluding wiring.						
[y]	Provision of Floor announceme								
[z]			e failure sensing for ARD along with auto						
	correction of phase reversal.	0.0	ramana danianing nan yuntu diana						
16	Landing entrance								
[a]	Location of landing entrance	:	All doors on the same side						
[]	in different floors	-							
[b]	Number	:	G, 2, 3, 4.						
[]			3, 2, 3,						
[c]	Size	:	Not less than 900 mm x 2000 mm [h]						
[d]	Type of doors	:	Horizontal sliding center opening						
[e]	Lift in use / lift out of order sign	:	A suitable box above the lift landing with						
			LED illuminated [in English / Hindi] sign of						
			"LIFT OUT OF ORDER" coming up						
			simultaneously at all floors						
17	Electric supply	:	[a] Power: 415 V, a.c., 3 phase, 50 Hz, 4						
			wire system						
			[b] Lighting: 230 V, 50 Hz, a.c.						
18	Is neutral wire available for	:	Yes						
	control circuits								
19	Proposed date for	:	As per contract						
	commencement on site								
20	Proposed date for completion	:	As per contract						
21	Environmental condition at	:	Summer condition						
	site of installation								
			Winter condition						
			Monsoon condition						
			Height above sea level						
22	Traction System	•	Rope-in- belt driven technology						
23	Fire Rating	:	2 Hours fire rating landing doors						
	-		(certification required)						
24	Car Flooring	:	Natural granite flooring						
25	Door sensor	:	Light curtain protection on door						
26	Car and landing operation	:	Tactile push button along with additional						
	panel		Braille inscriptions.						
27	Ventilation	:	Noiseless centrifugal type fans						
			(blowers) of appropriate throw of CFM						
			inside the car						
28	Mirror	:	Full length mirror on rear side						
29	Confirming to Quality		IS/ISO-9001:2015						
	Standard								



Mon of Em		

	IS/ISO-9001:2015						
30	IoT cloud-based device	OEM	itself	having	the	Intellectual	
		Property Rights					

SPECIAL CONDITION FOR MAIN COMPOSITE CONTRACTOR FOR EXECUTION OF LIFT.

1.1. The responsibility of execution of work of Lift shall lie with Main Contractor only. The contractor is required to furnish the documents/certificates in support of his experience to execute the mentioned E&M works given in Table-1 below after award of work. The main agency must associate OEM of Lift to execute the mentioned E&M component/components of the work having requisite experience as per table-1. In this connection, it is mentioned that the composite contractor and the OEM of Lift shall give required affidavit to confirm their association to the Engineer-in-charge. Tender accepting authority may approve change of subagency in case it is required during the currency of the contract.

The composite category contractor does not eligible directly to procure the equipment of approved make from manufacturer and get it installed from authorized agency/service provider of the manufacturer or specialized agency as per criteria mentioned in NIT, they must associate Specialized Agency/Agencies to undertake the specialized component/components of the work having requisite experience for individual works as mentioned below:

SI.	Sub	Eligibility cri	iteria -The ag	Definition of similar work	
No.	head	have success	fully completed		
	of	mentioned du	ring last seven y	ears ending	
	work	previous day	of		
		last date of su	bmission of Bid		
		Three	Two	One	
		similar	similar	similar	
		works each	works	work	
		of value not	each of	each of	
		less	value not	value	
		than(Rs.)	less		
			than(Rs.)		
1	Lift	42.44 Lakhs	63.65 Lakhs	84.87 Lakhs	Supply, installation,
					Testing and
					commissioning of Lift
					works.

Note: - All amounts rounded off to a convenient figure. The value of executed works shall be brought to current costing level by enhancing the actual value of work at simple rate of 7% per annum; calculated from the date of completion to the last date of submission of Bid.

1.2. Certificate of compliance of lift manufacturer to BIS standards duly certified by the manufacturer itself in notarized affidavit as per **Annexure-X1** in non-judicial stamp paper worth Rs. 200/-.

Page **49** of **64**



- 1.3. Undertaking from lift manufacturer regarding availability of spares for the entire life of lifti.e., for 20 years as per **Annexure-X2** as notarized affidavit in non-judicial stamp paper worth Rs. 200/-.
- 1.4. Certificate of compliance of the complete lift installation including its components, safety devices, various type of controls, etc. testing, inspection, operation and maintenance conform to relevant codes, standards, code of practices, guidelines, safety rules, Inspection manual(s), rules issued by Bureau of Indian Standards, as amended upto date in notarized affidavit in stamp paper worth Rs. 200/-
- 1.5. Certificate of quality standards conforming to IS/ISO- 9001: 2015.
- 1.6. The downtime of installed lifts, which are being maintained by the manufacturer, shall not be more than 8 hours (average) in case of minor faults and 7 days (average) in case of major faults in last one financial year self-certified in notarized affidavit in non-judicial stamp paper worth Rs. 200/-.
- 1.7. As per the conformity with statutory acts, rules, regulations, standards and safety codes, the Installation shall be carried out in conformity with the local lifts acts and rules, getting the necessary lift license from the concerned Government Department/ authority shall be in the scope of the Contractor.
- 1.8. The installation of IoT cloud-based device, The OEM itself having the Intellectual Property Rights.
- 1.9. The OEM itself having the capability to manufacture minimum number of 5,000 lifts per year at their manufacturing / works unit along with their own testing tower facility.
- 1.10. The OEM should have at least 1,000 passenger lift service and maintenance portfolio per year in in the Government Sector in Delhi.
- 1.11. The OEM must produce PERFORMANCE CERTIFICATES of at least 50 passenger lifts units, working in good condition installed in government buildings, the lifts should have commissioned atleast 05 years from the date of submission of bids, the certificate shall be from the Engineer-in-charge (Not below the rank of Executive Engineer).

Page 50 of 64



ANNEXURE - X1

UNDERTAKING FROM LIFT MANUFACTURER

(SELF CERTIFICATION IN CONFORMITY TO RELEVANT CODES AND STANDARDS ISSUED BY BIS)

We, M/s
1. IS 14665 (Part-1): 2000
2. IS 14665 (Part-2 / Section 1 & 2): 2000
3. IS 14665 (Part-3 / Section 1 & 2): 2000
4. IS 14665 (Part-4 / Section 1 to 9): 2001
5. IS 14665 (Part-5): 1999
6. IS 15785: 2007
7. IS: 15330: 2003
In addition to the above BIS Standards the entire lift installation and its individual components shall comply to all other relevant codes / Standards as applicable.
For M/S
(Authorized signatory of lift manufacturer)
(Authorized signatory of lift manufacturer)
Note: To be furnished on a 'Non-Judicial' stamp paper worth Rs. 200/

Page **51** of **64**



ANNEXURE - X2

UNDERTAKING FROM LIFT MANUFACTURER

(To be submitted prior to the supply of lift)

We stand guarantee for availability of spares for the entire life of the lift for a periodof minimumyears after completion of the installation or handing over of the lift whichever is later.
(Note: period shall be up to 20 years)
For M/S,
(Authorized signatory of lift manufacturer)

Note: To be furnished on a 'Non-Judicial' stamp paper worth Rs. 200/-



TECHNICAL PARTICULARS [To be filled & submitted by the bidder along with bid duly typed for each lift on OEM Letter Head.]

SI. No).	Particulars of details		
Α		General		
	1	Name of manufacturer	:	
	2	Country of manufacture	:	
	3	Capacities [persons / weight]	:	
	4	Service	:	
	5	Speed of travel	:	
	6	Height of travel	:	
	7	No. of floors served	:	
	8	No. of openings	:	
	9	Position of counterweight	:	
	10	Type of levelling method	:	
В		Machine		MR/ MRL [Whichever is best suited for respective site requirement].
	1	Position of machine & Control panel	:	
	2	Motor	:	
	3	Electric supply particulars for which	:	
		it is suitable for operation		
С		Brake		
	1	Туре	:	
D		Car and Doors		
	1	Outside dimensions of car	<u>:</u>	
	2	Inside clear dimensions	:	
	3	Construction of car	:	
	4	Design / type of enclosure of car	:	
	5	Details of flooring	<u>:</u>	
	6	Attachment and fitting inside the car	1:	
	7_	Car doors	-	
	[a]	Size	:	
	[b]	Operation	<u> </u> :	
	[c]	Construction, Design & finish	:	
	8	Landing Doors	-	
	[a]	Size	1:	
	[b]	Operation	1:	
	[c]	Construction, design & finish	1:	
E		Safety Devices	-	
	1	Car safety type	:	
	2	Counterweight safety type	:	
	3	Door inter locks in car-type	<u>:</u>	
	4	Door locks in landing-type	:	



	F	Traction system (whether rope in belt driven technology or not)	••	
		Landing door Fire rating in hours	•	
		Car flooring	÷	
		Whether light curtain door sensor	÷	
		provided or not	•	
		Whether Car and landing	:	
		operation panel touch sensitive,		
		stylish or not (please attach		
		brochure)		
		Whether flooring of car natural	:	
		granite		
		Whether centrifugal type noise	:	
		less fan provided in the car for		
		ventilation or not		
		Whether Communication and	:	
		additional features as per		
		Additional Specification (29)		
		complied		
	3	Communication Protocols	:	
	1	iBMS enabled with RS485		
		communication protocol.		
	2	IoT Cloud based device [OEM		
		having IPR].		
ŀ	1	Compliance		
	1	5,000 Lifts manufacturing		
		capability with testing tower		
		facility. [Certificate required]		
	2	Servicing Certificate of at least		
		1,000 units. [Certificate required]		
	3	Performance Certificate of at least		
1	1	50 units. [Certificate required]		

Signature with seal of bidder



INSTRUCTION TO BE DISPLAYED IN HINDI / ENGLISH IN THE LIFT CARS AND LIFT LANDINGS

Passenger Lift for Non-residential Buildings

Sr. No.	Inside the car	•	Sr. No.	Outside the car		
1	Lift number	:	1	Lift number	:	
2	Capacity [kg]	:	2	Capacity [kg]	:	
3	No smoking	:	3	Smoking not permitted inside the car	:	
4	Operate push buttons / switches	:	4	Passenger travel at their own risk	:	
5	Do not lean against the lift door	:	5	Watch before you step into and out of the lift car	:	
6	Watch before stepping out	:	6	Do not force open the landing door	:	
7	Do not panic in the event of breakdown. Press alarm buttons and follow instructions of authorised staff	:	7	Avoid use of lift during fire		
			8	Please stand in 'Q'	:	
			9	Please keep the lift neat and clean	:	
			10	Heavy articles / luggage not allowed	:	
			8	Complaints if any may be sent to	:	
			9	Hours of operation	:	



ANNEXURE - 1

<< Organization Letter Head >> **DECLARATION**

I/W	e,		hereby declare that all the information and data
furnis	shed by our organization with regard to	this	tender specification are true and complete to the best of
			specification, conditions and stipulations in details and
agre	e to comply with the requirements and i	nte	nt of specification.
1	Name & Address of the bidder	:	
2	Phone	:	
3	E-mail	:	
4	Contact person name	:	
5	Mobile number	:	
6	GSTIN number	:	
7	PAN number	:	
8	UTR no. [if deposited online] for EMD	:	
9	DD / FDR / Banker's Cheque No. [if	:	
	uploaded scanned copy] for EMD		
	BANK DETAILS of Bidder		
10	Bank name	:	
11	Branch address	:	
12	Branch telephone no.	:	
13	MICR Code of the bank	:	
14	IFSC code	:	
15	Bank Account no.	:	
16	Type of account	:	
We f	urther declare that our organization has	s no	ot been blacklisted / delisted or put to any holiday by any

Institutional agency / Govt. Department / Public Sector Undertaking in the last three years.

(Signature& name of the bidder) Seal of the bidder

Page **56** of **64**



BID SUBMISSION CHECK LIST

ONLINE BID SUBMISSION:

The Online bids (complete in all respect) must be uploaded online in **two** Envelops as explained below:-

SI. No.	SI. No. Documents Content								
1		Annexure – I duly filled in and duly mentioning UTR No. for EMD deposition or Banker's Cheque or Demand Draft or FDR number with date of issue and got signed	.PDF						
2	Technical Bid	Proof of EMD deposit / Scanned copy of DD submission (favouring 'Registrar, IIT Delhi') & Undertaking.	.PDF						
3	(Refer List of	Certificate of work experience as desired	.PDF						
4	Mandatory Documents to be	Ory Certificate of GST Registration & undertaking							
5	scanned and uploaded within	Affidavit as per provision of the clause 1.1.2 of IITD-6	.PDF						
6	the period of bid	the period of bid							
7	submission as given in the	IITD 7 / 8 duly signed	.PDF						
8	section INFORMATION	EPFO & ESIC Registration proof	.PDF						
9	& INSTRUCTION	Valid Electrical Licence	.PDF						
10	TO BIDDERS FOR E- TENDERING after Clause 24)	Technical Compliance sheet (Annexure – H) duly filled in and signed with Annexure X1 & X2 on OEM Letter Head along with manufacturing, servicing and performance certification required.	.PDF						
11	,	Certificate (that the OEM is complying with BIS standards) duly certified by designated labs / certifying agencies	.PDF						
12		Certificate in this regard that the OEM is PPP MII Order-2017 (as amended) compliant							
13		An undertaking on OEM letter head regarding availability of spares for the entire life of the lift	.PDF						

Page **57** of **64**



C ... Nil I Nil O Nil

14		Quality Standards certificates of OEM conforming to IS/ISO-9001:2015 (as amended)	.PDF	
15		Certificate on OEM letter head that the complete Lift installation including its components, safety device, various types of controls etc., testing, inspection, operation & maintenance shall conform to relevant Codes / Standard /Code of practices / Guidelines / Safety Rules / Inspection Manual (s) / Rule issued by Bureau of Indian Standards, as amended upto date	.PDF	
16		"The Down Time of installed lifts (mentioning details of capacity of lifts, date of commissioning, etc.), which are being maintained by the manufacturer, shall not be more than 8 hours (average) in case of minor faults and 7 days (average) in case of major faults in last one year. The data to be considered shall be for last financial year." – A certificate in this regard from the present client of OEM shall have to be enclosed with Technical bid.	.PDF	
17		Any other documents like product brochure, etc. as specified in the NIT	.PDF	
	Envelope – 2			
SI. No.	TYPES	Content		
1.	Financial Bid	Price bid should be submitted in BOQ format.	.EXL	

Sr.T.S JE / AE EE[ED-I]




SCHEDULE OF QUANTITY

Name of work: Replacement of 5 x 8 Passenger Lifts at different places in IIT Delhi.

	Of Work: Replacement of 5 x 8 Passenger I	-1115	at unit	Tent places	ווווו של	51111i
S. No.	Description of work		O41/	Rate	Unit	Amount
NO.	Sub Head - I	<u>'</u>	Qty	Rate	Offic	Alliount
1						
1	Supplying, installation, testing and commissioning of 8 passenger [544 kg] lifts					
	having contract speed of 1.5 MPS [referring					
	para 8 of specification for selection of					
	speed] serving different floors in the					
	existing lift shaft as per detailed					
	specifications enclosed in annexure 1 and					
	as under:					
1.1	Location of lifts: Multi-Storey Building, IIT					
	Delhi					
	[i] Speed : 1.5 MPS					
	[ii] Floors: 7					
	[iii] Travel: G + 6 [G, 1, 2, 3, 4, 5, 6]					
	[iv] Stops & opening: 7 nos.					
	[v] Controller: AC variable voltage &					
	variable frequency					
	[vi] Automatic rescue device complete with					
	dry maintenance free batteries as required.					
	[vii] Operation: Microprocessor based					
	single automatic push button duplex					
	collective selective with / without attendant					
	[viii] Power: 415 volt, 3 phase, 50 Hz, 4 wire					
	system					
	[ix] Type of doors:					
	[a] Car: Power operated, centre opening					
	horizontal sliding stainless steel scratch					
	proof [Linen finish]					
	[b] Landing doors: Stainless Steel [Linen					
	finish]					
	[x] A hand rail not less than 600 mm long at					
	900 mm above floor level to be fixed					
	adjacent to control panel in the lift car.					
	[xi] Voice announcement system in the car					
	to announce the position of the elevator in					
	the hoist way as the car passes or stops at					
	a floor served by the elevator.	2	nos.		each	
1.2	Location of lifts: Vishwakarma Bhawan, IIT					
	Delhi					


Page **59** of **64**





		 I	 I	 I		
	[i] Speed : 1.5 MPS					
	[ii] Floors: 7					
	[iii] Travel: B+G+6 [B, G, 1, 2, 3, 4, 5, 6]					
	[iv] Stops & opening: 8 nos.					
	[v] Controller: AC variable voltage &					
	variable frequency					
	[vi] Automatic rescue device complete with					
	dry maintenance free batteries as required.					
	[vii] Operation: Microprocessor based					
	single automatic push button simplex					
	collective selective with / without attendant					
	[viii] Power: 415 volt, 3 phase, 50 Hz, 4 wire					
	system					
	[ix] Type of doors:					
	[a] Car: Power operated, Centre/ telescopic					
	opening horizontal sliding stainless steel					
	scratch proof [Linen]					
	[b] Landing doors: Stainless Steel [Linen					
	finish]					
	[x] A hand rail not less than 600 mm long at					
	900 mm above floor level to be fixed					
	adjacent to control panel in the lift car. [xi] Voice announcement system in the car					
	to announce the position of the elevator in					
	the hoistway as the car passes or stops at					
	a floor served by the elevator.	1	nos.		each	
1.3	Location of lifts: Taxila Apartment, IIT Delhi	'	1103.		Cacii	
	[i] Speed: 1.5 MPS					
	[ii] Floors: 6					
	[iii] Travel: G + 5 [G, 1, 2, 3, 4, 5]					
	[iv] Stops & opening: 6 nos.		-			
	[v] Controller: AC variable voltage &					
	variable frequency		 			
	[vi] Automatic rescue device complete with					
	dry maintenance free batteries as required.		-			
	[vii] Operation: Microprocessor based single automatic push button simplex					
	collective selective with / without attendant					
	[viii] Power: 415 volt, 3 phase, 50 Hz, 4 wire		 			
	system					
	[ix] Type of doors:					
	[a] Car: Power operated, centre opening		-			
	horizontal sliding stainless steel scratch					
	proof [Linen finish]					
	Proof [Enfort millori]	l		1		

Page **60** of **64**





	[b] Landing doors: Stainless Steel [Linen/finish]				
	[x] A hand rail not less than 600 mm long at 900 mm above floor level to be fixed adjacent to control panel in the lift car.				
	[xi] Voice announcement system in the car to announce the position of the elevator in the hoistway as the car passes or stops at a floor served by the elevator.	1	nos.	each	
1.4	Location of lifts: Synergy building, IIT Delhi		11001		
	[i] Speed : 1.5 MPS				
	[ii] Floors: 4				
	[iii] Travel: G + 3 [G, 2, 3, 4]				
	[iv] Stops & opening: 4 nos.				
	[v] Controller: AC variable voltage & variable frequency				
	[vi] Automatic rescue device complete with				
	dry maintenance free batteries as required.				
	[vii] Operation: Microprocessor based				
	single automatic push button simplex				
	collective selective with / without attendant				
	[viii] Power: 415 volt, 3 phase, 50 Hz, 4 wire				
	system				
	[ix] Type of doors:				
	[a] Car: Power operated, centre opening horizontal sliding stainless steel scratch proof [Linen finish]				
	[b] Landing doors: Stainless Steel [Linen finish]				
	[x] A hand rail not less than 600 mm long at 900 mm above floor level to be fixed				
	adjacent to control panel in the lift car.				
	[xi] Voice announcement system in the car				
	to announce the position of the elevator in				
	the hoistway as the car passes or stops at		NI -	'	
2	a floor served by the elevator.	1	Nos.	each	
2	Dismantling and removal of existing (G+5)/(G+6)/(B+G+6), 8 passenger lift from				
	the shaft including removal of rail, car,				
	counter weight, traction motor, control				
	panel from lift machine room, other wires				
	and accessories etc. complete as directed				
	by the Engineer-in-charge.[Locations:-				
	MSB, Vishwakarma Bhawan, Taxila			_	
	Apartment]	4	Nos.	each	

Page **61** of **64**



~ 70 10**

3	Dismantling and removal of existing (G+3),					
	8 passenger lift from the shaft including					
	removal of rail, car, counter weight, traction					
	motor, control panel from lift machine room,					
	other wires and accessories etc. complete					
	as directed by the Engineer-in-					
	charge.[Locations:- Synergy Building]	1	nos.		each	
4	Necessary modification civil work for					
	accommodating the new lift of					
	(G+5)/(G+6)/(B+G+6), 8 passenger					
	capacity and its accessories in the existing					
	shaft, in landing doors, in machine room					
	etc. as required.[Locations:- MSB,					
	Vishwakarma Bhawan, Taxila					
	Apartment]	4	Job		Job	
5	Necessary modification civil work for					
	accommodating the new lift of (G+3), 8					
	passenger capacity and its accessories in					
	the existing shaft, in landing doors, in					
	machine room etc. as					
	required.[Locations:- Synergy Building]	1	Job		Job	
	(-) Less credit for dismantled lift					
	alongwith its all accessories. (Reserve					
	price is Rs.1,50,000/- for each lifts.					
	Bidder can't quote below the reserve					
	price set)	5	Lot		Lot	
	Sub Head - II (AMC)					
1	Comprehensive maintenance of 02 nos. 08					
	Passenger (G+6) lifts which include routine,					
	preventive and breakdown maintenance for					
	period of five years including repair /					
	replacement of worn out items with					
	minimum downtime and warranty &					
	guarantee of repaired / replaced items after					
	completion of one year guarantee					
	period.[Locations:- MSB Building]					
	1st Year (Free of cost, being Defect Liability					
	Period)	1	Job		Job	
			Job		Job	
	2nd Year	1	J00	<u> </u>	2	
	2nd Year 3rd Year	1	Job		Job	
		1 1 1				
	3rd Year	1	Job		Job	
	3rd Year 4th Year	1	Job Job		Job Job	
2	3rd Year 4th Year 5th Year	1	Job Job Job		Job Job	

Page **62** of **64**



	routine, preventive and breakdown				
	maintenance for period of five years				
	including repair / replacement of worn out				
	items with minimum downtime and				
	warranty & guarantee of repaired / replaced				
	items after completion of one year				
	guarantee period.[Locations:-				
	Vishwakarma Bhawan]				
	1st Year (Free of cost, being Defect Liability		1-1-	1-1-	
	Period)	1	Job	Job	
	2nd Year	1	Job	Job	
	3rd Year	1	Job	Job	
	4th Year	1	Job	Job	
	5th Year	1	Job	Job	
	6th Year	1	Job	Job	
3	Comprehensive maintenance of 01 nos. 08				
	Passenger (G+5) lifts which include routine,				
	preventive and breakdown maintenance for				
	period of five years including repair /				
	replacement of worn out items with				
	minimum downtime and warranty &				
	guarantee of repaired / replaced items after				
	completion of one year guarantee				
	period.[Locations:- Taxila Apartment]				
	1st Year (Free of cost, being Defect Liability Period)	1	Job	Job	
	2nd Year	1			
	3rd Year	•	Job	Job	
		1	Job	Job	
	4th Year	1	Job	Job	
	5th Year	1	Job	Job	
	6th Year	1	Job	Job	
4	Comprehensive maintenance of 01 nos. 08				
	Passenger (G+3) lifts which include routine,				
	preventive and breakdown maintenance for				
	period of five years including repair /				
	replacement of worn out items with				
	minimum downtime and warranty &				
	guarantee of repaired / replaced items after				
	completion of one year guarantee period.[Locations:- Synergy Building]				
	1st Year (Free of cost, being Defect Liability				
	Period)	1	Job	Job	
	2nd Year	1	Job	Job	
	3rd Year	1	Job	Job	
-	4th Year	-			
1	Hui i Cai	1	Job	Job	1

Page **63** of **64**



 $Tender\ Document\ for\ Replacement\ of\ 5\ x\ 8\ Passenger\ Lifts\ at\ different\ places\ in\ IIT\ Delhi.$

5th Year	1	Job	Job	
6th Year	1	Job	Job	
TOTAL (Rs.)				*****

JE[E] EE [EED-I]