## INDIAN INSTITUTE OF TECHNOLOGY HAUZ KHAS, NEW DELHI-110 016

### Date: 26-10-2015

### **NOTICE INVITING QUOTATIONS**

### Subject: Thermal Evaporation coating unit

Indian Institute of Technology Delhi invites sealed tender offers in two bid format (Technical bid and Commercial bid) from eligible and experienced OEM (Original Equipment Manufacturer) OR OEM Authorized Dealer for **Thermal Evaporation coating unit** with three years on site comprehensive warranty from the date of receipt of the material as per terms & conditions specified in the tender document.

# The quotations plus additional details should reach by 5:00 P.M. on 16 November 2015 (Monday).

### **TECHNICAL SPECIFICATION:**

#### **TECHNICAL SPECIFICATION:**

S. No.	Feature	Specification	
1.	General	1. The equipment is to be used for vacuum evaporation of metals on to	
	Description	a substrate.	
		2. The evaporation is to be done in a high vacuum contamination free	
		chamber.	
2.	Vacuum	The cylindrical chamber made out of stainless steel with high vacuum	
	Chamber	sealing and hydraulic lifting mechanism. The chamber has two numbers	
		of 3 "port at right angles and fixed with toughened glass to view inside.	
		a. Nominal Internal Diameter : 300 mm	
		c. Nominal Height : 450 mm	
3.	Base Plate	A base plate of 13" dia is made out of SS 304 material, finely ground	
		and electro chemically polished to achieve a fine surface finish to seal	
		with an L-gasket fixed on the bell jar.	
4.	Chamber Gadge	getories	
i.	L.T.	Three (3) set of LT evaporation feed through shall be provided for	
	Evaporation	thermal evaporation. Each feed through shall have independent DC	
	feed through	power supply with common ground. Three separate Variacs should be	
	(filament	provided for controlling.	
	holder)		
ii.	Evaporation	Three set of evaporation source Holder. These can accept	
	Source Holder	Filament/Basket/Boat evaporation sources.	
iii.	H.T. Ion clean	One HT electrical insulted feed through which can carry 5 KV power	
	feed through	for Ion bombardment. For Ion cleaning/bombardment of substrate. An	
	and Cleaning	annular (bar type) aluminium cathode for ion cleaning/bombardment	
	Gadget	with the spherical work holder.	
iv.	Source Shutter	Special source shutter is designed to cover or uncover simultaneously	
		the two sets of sector filament holders used with rotary work holder.	
		This shutter can be attached to the standard shaft seal.	
٧.	Substrate	Substrate heater system which can give a maximum of 800°C with	
	Heater	Kanthal element and digital PID controller.	

vi.	Digital film	4 digit LED display, Range: 0.000 to 999.9 K Å.
	thickness	
ļ	monitor	
5.	Vacuum Pumping System	
i.	Direct drive	a. Free air displacement Capacity (Meter cube per hour) :15 (250
	rotary pump	lit/min capacity) b. Ultimate vacuum when measured on a McLeod gauge with gas
		ballast Closed(m. bar) as per pnuerope standard: $>1x10-3$
		c. Motor (HP) (Single phase) : <sup>1</sup> / <sub>2</sub>
ii.	Oil Diffusion	a. Nominal diameter (mm) : 114
		b. Ultimate vacuum (m. bar) :> $5x10-6$
	pump	c. Effective Pumping Speed (lit/sec) : 500
		d. Type of jet : Fractionating
		e. No. of stages : 2
		f. Oil charge (cc) : 100
		g. Heater rating (watts) : 500
		h. Water circulation : 3-4 lit/min
6.	Vacuum	<b>a</b> . Digital pirani gauge with two Pirani gauge heads to independently
0.	Measuring	monitor the roughing (chamber) and backing pressure. Vacuum is the
	Gauges	chamber or pipe line can be seen on the gauge display using a selector
		switch. This pirani gauge can measure vacuum level from 0.5 m. bar
		to 0.0001 m. bar.
		<b>b</b> . Penning gauge with one gauge head to monitor high vacuum on a
		separate Penning meter in two ranges, from 1 x 10-3 to 1 x 10-5 m.
		bar and from 2 x 10-5 to 1 x 10-6 m. bar.
7.	L.T. power	Three L.T. power supply units, which can be controlled separately.
	Supply	Each power supply consists of a transformer capable of delivering 200
	11.	amps at 10 volts.
8.	H.T. power	H.T. power supply is provided and it consists of 5000 volts DC open
	Supply	circuit, 3500 volts and 50 mA. High reactance type transformer and
		solid state bridge rectifier.
9.	L.T/H.T.	Separate Dimmer stats should be provided in the LT/HT circuit for
	Controls and	output power variation. Separate meters are provided for LT/HT
	Meters	current read out.
10.	Power	To connect the power to the system 5 meters long 15 amps 3 wire
	Connections	chord with plug shall be provided.
11.	Installation	Installation should be carried out by trained personnel. Installation
		includes complete fitting, fixing and testing.
12.	Warranty	Three years warranty against all manufacturing defects.

# **Additional Details:**

1. Please furnish brochure cum data sheets from the original manufacturer for the specifications of the item quoted, or better; without this, quotation will be rejected.

**2.** Please furnish a list of recent customers (Address, Email & Phone No.) where the specific product has been supplied, if any.

### TERMS & CONDITIONS COVERING SUBMISSION OF QUOTATIONS:

**1. PRICE:** The price should be quoted in net per unit (after breakup) and must include all packing and delivery charges. The offer/bid should be exclusive of taxes and duties, which will be paid by the purchaser as applicable. However the percentage of taxes & duties shall be clearly indicated.

The price should be quoted without custom duty and excise duty, since IIT Delhi is exempted from payment of Excise Duty and is eligible for concessional rate of custom duty. Necessary certificate will be issued on demand.

In case of import supply the price should be quoted on FOB Basis only. Under special circumstances (eg. perishable chemicals), when the item is imported on CIF, please indicate CIF charges separately upto IIT Delhi indicating the mode of shipment. IIT Delhi will make necessary arrangements for the clearance of imported goods at the Airport/Seaport. Hence the price should not include the above charges.

**2. DISCOUNT/REBATES:** Special discount/rebate wherever admissible, keeping in view that the supply is being provided for educational purpose in respect of public institution of national importance, may please be indicated.

3. TERMS OF PAYMENT: Payment against delivery (Wire Transfer after receipt of item).

**4. VALIDITY OF QUOTATIONS:** Quotations should be valid at least for a period of **90** days.

**5. DEALERSHIP CERTIFICATE:** Letter from manufacturer to be attached for authenticity of Dealership/agency. Quotations without authorized dealership certificate will be rejected. Please note that either the manufacturer or the authorized dealer can submit quotation, but both cannot submit quotation for the above item.

**6. PROPRIETARY CERTIFICATE:** If the items are proprietary in nature, please furnish a copy of the proprietary certificate.

**7. COMPLIANCE STATEMENT:** Please include a statement of compliance for all the above specifications.

**8**. **CORRESPONDANCE:** No correspondence regarding acceptance/rejection of a quotation will be entertained.

**9. INSTITUTE'S RIGHTS:** IIT Delhi reserves the rights of acceptance or rejection of any or all Quotations.

Quotations may please be sent to:

Prof. R. K. Soni Department of Physics Indian Institute of Technology, Hauz Khas, New Delhi - 110016 India. Fax: +91-11-26581114 E-mail: ravisoni@physics.iitd.ac.in